



SAFETY DATA SHEET

KCDA # 38117

Revision Date 06/09/2015

REVISION NUMBER: 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name 108 GLS GLASS CLEANER PLUS, Mirrors & Glass Cleaner

Other means of identification

Product code 117663
UN/ID No. 1950
Synonyms NONE

Recommended use of the chemical and restrictions on use

Recommended Use No information available.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address
See Distributor information.

Importer
Rochester Midland Limited
5353 John Lucas Drive
Suite 103
Burlington, ON L7L 6G5
Canada

Distributor
Rochester Midland Corporation
155 Paragon Drive
Rochester, New York 14624 USA

Emergency telephone number

EMERGENCY TELEPHONE INFOTRAC: 1-800-535-5053
OUTSIDE U.S.: +1-352-323-3500
CANUTEC: 613-996-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| | |
|----------------------|---------------|
| Gases under pressure | Liquefied gas |
|----------------------|---------------|

Label elements

Emergency Overview

WARNING
Contains gas under pressure; may explode if heated



Appearance Clear

Physical state Aerosol Compressed
liquefied gas

Odor Butyl odor

Precautionary Statements - Storage

Protect from sunlight. Store in a well-ventilated place

Hazards not otherwise classified (HNOC)

No information available

Other Information

3. COMPOSITION/INFORMATION ON INGREDIENTS

| PRODUCT COMPOSITION | CAS No. | % | TRADE SECRET |
|---------------------|----------|----------|--------------|
| 2-Butoxyethanol | 111-76-2 | 2.5 - 10 | * |
| Ethyl alcohol | 64-17-5 | 2.5 - 10 | * |
| Butane | 106-97-8 | 1 - 2.5 | * |
| Propane | 74-98-6 | 1 - 2.5 | * |

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

- General advice** No hazards which require special first aid measures.
- Eye contact** IF IN EYES: Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
- Skin contact** IF ON SKIN: Wash with soap and water.
- Inhalation** IF INHALED: Remove to fresh air.
- Ingestion** IF SWALLOWED: Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Water fog, carbon dioxide, foam, dry chemical.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Explosion data

Sensitivity to Mechanical Impact NONE.

Sensitivity to Static Discharge NONE.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do it without risk. Cool exposed containers with water spray. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible withdraw from area and let fire burn.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions

Evacuate personnel to safe areas. Wear adequate personal protective equipment, see Section 8, Exposure Controls/Personal Protection. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate affected area. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Environmental precautions

Environmental precautions

Keep out of drains, sewers, streams, or other bodies of water. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment

Prevent further leakage or spillage if safe to do so. Stop the flow of gas or remove cylinder to outdoor location if this can be done without risk. If leak is in container or container valve, contact the appropriate emergency telephone number in Section 1.

Methods for cleaning up

Following product recovery, flush area with water.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Contents under pressure. Never pierce, drill, grind, cut, saw or weld any empty container. Do not smoke. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Bond and ground during liquid transfer. Do not reuse container. Avoid contact with skin and eyes. Use only with adequate ventilation. Use personal protection recommended in Section 8. Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Protect from sunlight. Store at temperatures not exceeding 50 °C/ 122 °F. Do not store near heat, sparks or flame.

Incompatible materials

None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

| PRODUCT COMPOSITION | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|---------------------|-----------|----------|------------|
|---------------------|-----------|----------|------------|

| | | | |
|-----------------------------|----------------|--|----------|
| 2-Butoxyethanol 111-76-2 | TWA: 20 ppm | S* (vacated) S* (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ TWA: 50 ppm TWA: 240 mg/m ³ | 700 ppm |
| Ethyl alcohol 64-17-5 | STEL: 1000 ppm | (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³ TWA: 1000 ppm TWA: 1900 mg/m ³ | 3300 ppm |
| Butane 106-97-8 | STEL: 1000 ppm | (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³ | - |
| Propane 74-98-6 | TWA: 1000 ppm | (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³ TWA: 1000 ppm TWA: 1800 mg/m ³ | 2100 ppm |

Appropriate engineering controls

ENGINEERING CONTROLS Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Safety glasses are recommended to minimize eye contact.

Skin and body protection Chemical resistant gloves are recommended to minimize skin contact. Appropriate protective clothing as needed to prevent skin contact. It is the responsibility of the end user of this product to determine level of PPE required that is consistent with safe use of this product.

RESPIRATORY PROTECTION None normally required. Use approved NIOSH respiratory protection if TLV/PEL exceeded or if over exposure is likely.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|--------------------------------------|----------------------------------|-------------------------|--------------------------|
| Physical state | Aerosol Compressed liquefied gas | Odor | Butyl odor |
| Appearance | Clear | Odor threshold | No information available |
| Color | Colorless or Light Yellow | | |
| Property | Values | Remarks • Method | |
| pH | 10.0 | +/- 0.5 | |
| Melting point/freezing point | No information available | | |
| Boiling point / boiling range | 100 °C / 212 °F | | |
| Flash point | No information available | | |
| Evaporation rate | No information available | | |
| Flammability (solid, gas) | No information available | | |
| Flammability Limit in Air | | | |
| Upper flammability limit: | No information available | | |
| Lower flammability limit: | No information available | | |
| Vapor pressure | No information available | | |
| Vapor density | No information available | | |
| Specific gravity | 0.97 | | |
| Water solubility | No information available | | |
| Solubility in other solvents | No information available | | |
| Partition coefficient | No information available | | |
| Autoignition temperature | No information available | | |
| Decomposition temperature | No information available | | |
| Kinematic viscosity | No information available | | |
| Dynamic viscosity | No information available | | |

Explosive properties No information available
Oxidizing properties No information available

Other Information

Softening point No information available
VOC (EPA METH.24) (G/L): No information available
Density No information available
Bulk density No information available

10. STABILITY AND REACTIVITY

REACTIVITY

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

CONDITIONS TO AVOID

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information No data available

Inhalation No data available.

Eye contact May cause slight irritation.

Skin contact Prolonged contact may lead to irritation and dermatitis.

Ingestion Large amounts may cause irritation, nausea, diarrhea.

| PRODUCT COMPOSITION | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-----------------------------|---------------------|------------------------|------------------------------------|
| 2-Butoxyethanol 111-76-2 | = 470 mg/kg (Rat) | = 220 mg/kg (Rabbit) | = 450 ppm (Rat) 4 h |
| Ethyl alcohol 64-17-5 | - | - | = 124.7 mg/L (Rat) 4 h |
| Butane 106-97-8 | - | - | = 658 g/m ³ (Rat) 4 h |
| Propane 74-98-6 | - | - | = 658 mg/L (Rat) 4 h |

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

| PRODUCT COMPOSITION | ACGIH | IARC | NTP | OSHA |
|-----------------------------|-------|---------|-------|------|
| 2-Butoxyethanol 111-76-2 | A3 | Group 3 | - | - |
| Ethyl alcohol 64-17-5 | A3 | Group 1 | Known | X |

Reproductive Toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

12. ECOLOGICAL INFORMATION

Ecotoxicity

| PRODUCT COMPOSITION | Algae/aquatic plants | Fish | Crustacea |
|-----------------------------|----------------------|--|--|
| 2-Butoxyethanol 111-76-2 | - | 2950: 96 h Lepomis macrochirus mg/L LC50 1490: 96 h Lepomis macrochirus mg/L LC50 static | 1000: 48 h Daphnia magna mg/L EC50 |
| Ethyl alcohol 64-17-5 | - | 12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static | 2: 48 h Daphnia magna mg/L EC50 Static 9268 - 14221: 48 h Daphnia magna mg/L LC50 |

Persistence and degradability
 No information available.

Bioaccumulation
 No information available.

| PRODUCT COMPOSITION | Partition coefficient |
|-----------------------------|-----------------------|
| 2-Butoxyethanol 111-76-2 | 0.81 |
| Ethyl alcohol 64-17-5 | -0.32 |
| Butane 106-97-8 | 2.89 |
| Propane 74-98-6 | 2.8 |

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Do not reuse container. Pressurized container: Do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

DEPT. OF TRANSPORTATION

UN/ID No. 1950
 Proper shipping name AEROSOLS, NONFLAMMABLE (each not exceeding 1 L capacity)
 Hazard Class 2.2
 Description 5 Liters (1.3 Gallons) and Less may be Classed as LTD. QTY.

TDG

UN/ID No. 1950
 Proper shipping name AEROSOLS, NONFLAMMABLE (each not exceeding 1 L capacity)
 Hazard Class 2.2
 Description 1 Liter (0.26 Gallons) and Less may be classed as LTD. QTY.

| |
|-----------------------------------|
| 15. REGULATORY INFORMATION |
|-----------------------------------|

International Inventories

| | |
|---------------|----------|
| TSCA | Complies |
| DSL/NDSL | Complies |
| EINECS/ELINCS | Complies |
| ENCS | Complies |
| IECSC | Complies |
| KECL | Complies |
| PICCS | Complies |
| AICS | Complies |

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| PRODUCT COMPOSITION | SARA 313 - Threshold Values % |
|----------------------------|-------------------------------|
| 2-Butoxyethanol - 111-76-2 | 1.0 |

SARA 311/312 Hazard Categories

| | |
|-----------------------------------|-----|
| ACUTE HEALTH HAZARD | No |
| CHRONIC HEALTH HAZARD | No |
| FIRE HAZARD | No |
| Sudden release of pressure hazard | YES |
| REACTIVE HAZARD | No |

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

| PRODUCT COMPOSITION | CA PROP 65: |
|-------------------------|-------------------------|
| Ethyl alcohol - 64-17-5 | Listed Developmental |

U.S. State Right-to-Know Regulations

| PRODUCT COMPOSITION | NJRTK: | MARTK: | PARTK: |
|-----------------------------|--------|--------|--------|
| 2-Butoxyethanol 111-76-2 | Listed | Listed | Listed |
| Ethyl alcohol 64-17-5 | 0844 | Listed | Listed |
| Butane 106-97-8 | 0273 | Listed | Listed |
| Propane 74-98-6 | 1594 | Listed | Listed |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA

Health hazards 1
 Flammability 0
 Instability 0
 Physical and Chemical Properties -

HMS

Health hazards 1
 Flammability 0
 Physical hazards 0
 Personal protection B

Revision Date 06/09/2015

Revision Note

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

*** END OF SDS ***