

# MATERIAL SAFETY DATA SHEET

23360

Fig. 1 313200

(APPROVED BY THE U.S. DEPARTMENT OF LABOR AS "essentially similar" to form OSHA-20 (former LSB-OSS-4) FOR HAZARDOUS PRODUCTS USED IN PLACES OF EMPLOYMENT

**Section 1 NAME AND PRODUCT** #268 Stencil Cement

<b>MANUFACTURER'S NAME</b>		<b>EMERGENCY PHONE NO.: 24 HOURS</b>
(a) A.B.DICK COMPANY		(b) 312-647-8800
<b>STREET ADDRESS</b>		<b>DATE THIS FORM WRITTEN</b>
(c) 5700 WEST TOUHY AVENUE	For latest data, consult manufacturer.	(d) April 24, 1985
<b>CITY, STATE, ZIP CODE</b>		<b>SIGNATURE</b>
(e) CHICAGO, ILLINOIS 60648		(f) Kenneth W. Pinter <i>Kenneth W. Pinter</i>

**CHEMICAL NAME, TRADE NAME, AND SYNONYMS**  
(g)

**HAZARD CLASSIFICATION FOR DEPARTMENT OF TRANSPORTATION (DOT)**

Flammable Liquid  Combustible Liquid  Corrosive Material  \_\_\_\_\_

DOT Shipping Name \_\_\_\_\_ Not regulated. \_\_\_\_\_ UN# \_\_\_\_\_

**Section 2 HAZARDOUS INGREDIENTS**

HAZARDOUS INGREDIENTS	CAS Reg. No.	% Wt.	TLV (units)
1. Butyl Alcohol (Z-1)	71-36-3	28-32	100 ppm
1,1,1-Trichloroethane (Z-1)	71-55-6	46-50	350 ppm

**Section 3 PHYSICAL DATA**

PHYSICAL DATA	pH	FREEZING POINT (°F)
2. BOILING POINT (°F.) Range	158 - 220	6. SPECIFIC GRAVITY (H <sub>2</sub> O = 1)
3. VAPOR PRESSURE (mmHg at 20°C)		7. % VOLATILE BY VOLUME
4. VAPOR DENSITY (air=1)	>1	8. COLOR AND ODOR
5. SOLUBILITY IN WATER	Insoluble	9. PHYSICAL STATE
		Liquid

**Section 4 FIRE AND EXPLOSION HAZARD DATA**

10. FLASH POINT (AND METHOD USED) >165 °F T.O.C., C.C.O., C.O.C.

11. FLAMMABLE LIMITS (STP)  
L.F.L. \_\_\_\_\_ U.F.L. \_\_\_\_\_

12. EXTINGUISHING MEDIA:  
 WATER FOG  FOAM  ALCOHOL FOAM  CO<sub>2</sub>  DRY CHEMICAL  
 OTHER \_\_\_\_\_

13. SPECIAL FIRE FIGHTING PROTECTIVE EQUIPMENT  
N.A.

14. UNUSUAL FIRE AND EXPLOSION HAZARDS  
N.A.

**Section 5 REACTIVITY DATA**

15. STABILITY

NORMAL CONDITIONS	OK
FIRE CONDITIONS	OK

16. CONDITIONS TO AVOID

17. INCOMPATIBILITY (Materials to avoid)  
 WATER  ACID  BASE  CORROSIVE  Strong OXIDIZING MATERIAL  
 OTHER \_\_\_\_\_

18. HAZARDOUS DECOMPOSITION PRODUCTS  
N.A.

19. HAZARDOUS POLYMERIZATION

MAY OCCUR	
WILL NOT OCCUR	X

20. CONDITIONS TO AVOID

## Material Safety Data Sheet - (continued)

## Section 6 HEALTH HAZARD DATA

## 21. ORAL INGESTION

Induce vomiting. Consult a physician.

## 22. EYE CONTACT

Flush with water. Seek medical attention.

## 23. SKIN CONTACT

If dried, remove with rubbing alcohol or nail polish remover; wash well with soap and water

## 24. SKIN ABSORPTION

See Item 23; no health hazard.

## 25. INHALATION (TLV OR SUGGESTED CONTROL FIGURE)

Not established.

## 26. EFFECTS OF OVEREXPOSURE

Headache; drowsiness.

## 27. FIRST AID PROCEDURES

## Section 7 SPILL OR LEAK PROCEDURES

## 28. STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wipe up with dry cloth or cloth dampened with alcohol.

## 29. DISPOSAL METHOD

Dried material with general office wastes.

## Section 8 SPECIAL PROTECTION INFORMATION

30. VENTILATION	LOCAL EXHAUST Sufficient	SPECIAL
	MECHANICAL (General)	OTHER

## 31. RESPIRATORY PROTECTION (Specify Type)

None required.

## 32. PROTECTIVE CLOTHING

None required.

## 33. EYE PROTECTION



NOT NORMALLY NECESSARY



SAFETY GLASSES WITHOUT SIDE SHIELDS



CHEMICAL WORKERS GOGGLES



GAS TIGHT GOGGLES OR EQUIVALENT



SAFETY GLASSES WITH SIDE SHIELDS



OTHER \_\_\_\_\_

## 34. OTHER PROTECTIVE EQUIPMENT

## Section 9 SPECIAL PRECAUTIONS OR OTHER COMMENTS

## 35. PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

## 36. OTHER PRECAUTIONS

Keep out of reach of children.