

31697

MATERIAL SAFETY DATA SHEET

Johnson wax
PROFESSIONAL

POWER FOAM BRAVO

HMIS		NFPA	Personal protective equipment		
Health	3	3			
Fire Hazard	4	4			
Reactivity	0	0			

Version Number: 1

Preparation date: 2006-02-08

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: POWER FOAM BRAVO

MSDS #: 114640002
Product code: 114640002, 04640
Recommended use: Floor care.

Manufacturer, importer, supplier:

US Headquarters
JohnsonDiversey, Inc.
8310 16th St.
Sturtevant, Wisconsin 53177-0902
Phone: 1-888-352-2249
MSDS Internet Address:
www.johnsondiversevy.comCanadian Headquarters
JohnsonDiversey - Canada, Inc.
2401 Bristol Circle
Oakville, Ontario L6H 6P1
Phone: 1-800-668-3131

Emergency telephone number: 1-800-851-7145 (Prosar); 1-651-917-6133 (Int'l Prosar); 01-800-710-3400 (México)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER. CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED. CONTENTS UNDER PRESSURE.

Principle routes of exposure: Eye contact. Skin contact. Inhalation. Ingestion.
 Eye contact: Corrosive. Causes permanent eye damage, including blindness.
 Skin contact: Corrosive. May cause permanent damage.
 Inhalation: May cause irritation and corrosive effects to nose, throat and respiratory tract.
 Ingestion: Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS

Ingredient(s)	CAS #	Weight %	LD50 Oral - Rat	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
2-butoxyethanol	111-76-2	5 - 10%	= 470 mg/kg	= 220 mg/kg	= 2.21 mg/L (4h) = 450 ppm (4h)
Sodium hydroxide	1310-73-2	1 - 5%	= 140 mg/kg	= 1350 mg/kg	Not available
Monoethanolamine	141-43-5	1 - 5%	= 1720 mg/kg	= 1 mL/kg	Not available

4. FIRST AID MEASURES

Eye contact: Immediately flush eyes with running water for at least 15-20 minutes, keeping eyelids open. Get medical attention immediately.
 Skin contact: Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
 Inhalation: If breathing is affected, remove to fresh air. Get medical attention immediately.
 Ingestion: Immediately drink one cupful of water or milk. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call medical attendant, medical doctor, or poison control center.
 Aggravated Medical Conditions: Persons with pre-existing skin disorders may be more susceptible to irritating effects

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: Use dry chemical, CO2, water spray or "alcohol" foam.
 Specific hazards: Aerosol product - Containers may rocket or explode in heat of fire. Keep product and empty container away from heat and sources of ignition. NFPA 30B Level 1 Aerosol.
 Unusual hazards: Corrosive material (See sections 8 and 10).
 Specific methods: Aerosol Product - Containers may rocket or explode in heat of fire. Use water spray to keep fire-exposed containers cool.

POWER FOAM BRAVO

1 of 4

5. FIRE-FIGHTING MEASURES

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: No information available

6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:
Environmental precautions
and clean-up methods:**

Use personal protective equipment
Remove all sources of ignition. Sweep up and shovel into suitable containers for disposal. Use a water rinse for final clean-up.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mists or dusts. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Use only with adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. CONTENTS UNDER PRESSURE. Do not puncture or incinerate. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Storage:

Store in a cool, dry, well ventilated area away from heat or open flame. Protect from freezing. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 degrees C or 120 degrees F. Do not pierce or burn, even after use. Keep out of the reach of children. NFPA 30B Level 1 Aerosol

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection:

Chemical splash goggles.

Hand protection:

Chemical resistant gloves

Skin and body protection:

Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice

Ingredient(s)	CAS #	ACGIH	OSHA	Mexico
2-butoxyethanol	111-76-2	20 ppm (TWA)	Skin 240 mg/m ³ (TWA) 50 ppm (TWA)	75 ppm (STEL) 360 mg/m ³ (STEL) 120 mg/m ³ (TWA) 26 ppm (TWA)
Sodium hydroxide	1310-73-2	2 mg/m ³ (Ceiling)	2 mg/m ³ (TWA)	2 mg/m ³ (Ceiling)
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m ³ (TWA)	15 mg/m ³ (STEL) 6 ppm (STEL) 3 ppm (TWA) 8 mg/m ³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Compressed gas
pH: 13
Appearance: Aerosol
Color: Clear Colourless
Odor: Solvent
Specific gravity: 0.99
Density: 8.26
VOC: 15.85
Flash point: <20 (°F) <-7 (°C)
Solubility: Soluble
Viscosity: No information available

Bulk density: 8.24
Dilution pH: NA
Vapor density: No information available
Evaporation Rate: No information available
Boiling point/range: Not determined
Melting point/range: Not determined
Decomposition temperature: Not determined
Autoignition temperature: No information available
Partition coefficient (n-octanol/water): No information available
Solubility in other solvents: No information available
Elemental Phosphorus: 0.11 %P

Flame Extension (Inches): 0

10. STABILITY AND REACTIVITY

Stability: The product is stable
Polymerization: Hazardous polymerization does not occur
Hazardous decomposition products: None reasonably foreseeable.

10. STABILITY AND REACTIVITY

Materials to avoid: Acids. Metals.
Conditions to avoid: Keep away from heat. Keep away from open flames, hot surfaces and sources of ignition. Do not freeze.

11. TOXICOLOGICAL INFORMATION

Acute toxicity Corrosive Oral LD50 estimated to be > 2000 mg/kg
Component Information: See Section 3
Chronic toxicity: None known
Specific effects
Carcinogenic effects: None known
Mutagenic effects: None known
Reproductive toxicity: None known
Target organ effects: None known

12. ECOLOGICAL INFORMATION

Environmental Information: No data available

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:
 Dispose of according to all federal, state and local applicable regulations
RCRA Hazard Class: D001

14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL), Australia (AICS), Korea (ECL), Philippines (PICCS), China (IECSC).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

Ingredient(s)	CAS #	MARTK:	NJRTK:	PARTK:	RIRTK:
2-butoxyethanol	111-76-2	X	X	X	X
Sodium hydroxide	1310-73-2	X	X	-	X
Monoethanolamine	141-43-5	X	X	X	X
Ethoxylated alkylphenol	68412-54-4	-	-	-	-
Water	7732-18-5	-	-	-	-
Isobutane	75-28-5	X	X	X	-

CERCLA/ SARA

Ingredient(s)	CAS #	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
2-butoxyethanol	111-76-2	5 - 10%			X
Sodium hydroxide	1310-73-2	1 - 5%	1000		

SARA 311/312 Hazard Categories

Immediate: Y
Sudden Release of Pressure: Y

Canada

WHMIS hazard class: A Compressed gases, E Corrosive material.



Ingredient(s)	CAS #	NPRI
2-butoxyethanol	111-76-2	X
Ethoxylated alkylphenol	68412-54-4	X

16. OTHER INFORMATION

Reason for revision: Not applicable
Prepared by: NAPRAC
Additional advice: None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.