



#37796 + 37797

Page 1

ENVIRO CARE

Conseal Concrete/Stone Protective Coating

Product Safety Information Sheet (MSDS)

This Product Safety Information Sheet is principally directed to managerial, safety, hygiene and medical personnel. The description of physical, chemical and toxicological properties and handling advice is based on experimental results and anticipated exposure.

This Product Safety Information Sheet meets the material safety data sheet (MSDS) requirements of the federal OSHA Hazard Communication Standard (29 CFR 1910.1200).

NFPA 704 Rating

Health 0
Flammability 0
Reactivity 0

Key

0 = Minimal
1 = Slight
2 = Moderate
3 = High
4 = Extreme

I. INGREDIENTS

Diethylene glycol monobutyl ether 5-10%
CAS Reg. No. 112-34-5 TLV not established

Ethylene glycol 1-5%
CAS Reg. No. 107-21-1 TLV 5 ppm

II. PHYSICAL PROPERTIES

Appearance: Enviro Care Concrete/Stone Protective Coating is a free-flowing, white opaque liquid with a mild acrylic odor.

Boiling Point: 212° F.

Specific Gravity: 1.02 (8.5 lbs/gallon)

pH: 7.3

Percent Volatile: 75

Solubility in Water: Complete

III. FIRE HAZARD

Enviro Care Conseal Concrete/Stone Protective Coating is not considered a fire hazard, nor will it support combustion.

Use standard firefighting techniques to extinguish fires involving this material (water spray, dry chemicals or foam).

Corporate Headquarters
1015 North 14th Street
Omaha, Nebraska 68102
(402) 342-4248
(800) 877-7200
FAX 1-402-342-3706

37796, 37797

IV. REACTIVITY DATA

Enviro Care Conseal Concrete/Stone Protective Coating is stable and non-reactive.

V. HEALTH HAZARD DATA

The principal route of exposure to Enviro Care Conseal Concrete/Stone Protective Coating is skin contact. Skin or eye contact may cause irritation. May be harmful if swallowed.

Enviro Care Conseal Concrete/Stone Protective Coating is not listed as a carcinogen by NTP, IARC or OSHA.

VI. FIRST AID

For eye contact, flush with clear water for 15 minutes. For skin contact, wash with soap and water. If swallowed, or if any irritation persists, consult a physician.

VII. PRECAUTIONS FOR SAFE HANDLING AND USE

Keep out of reach of children. Avoid eye and prolonged skin contact. Use with adequate ventilation.

VIII. SPILL HANDLING

If Enviro Care Conseal Concrete/Stone Protective Coating is spilled, recover liquid with wet mop or wet/dry vacuum. Flush residue to sewer with water. Use care, as floor may become slippery.

IX. SPECIAL PROTECTION INFORMATION

Protective equipment is not normally required. If desired, rubber, neoprene or vinyl gloves may be used to minimize skin contact. Splashproof chemical safety goggles may be used to eliminate the possibility of eye contact.

New Issue: 2/90