

Date of Preparation: September 16, 1988

SECTION I

Manufacturer : Binney & Smith Company
 Address : P.O. Box 546
 Winfield, Kansas 67156
 Telephone : 316-221-4200
 Emergency : 316-221-4200
 Product Class: Artist Oil Paints
 Mfg. Code ID : Series 1144

- H M I S -

Health	: 2
Flammability	: 0
Reactivity	: 0
Personal Protection	: *



Conforms
 ASTM D423
 & D4302

(HAZARD RATING: 0=least, 1=slight, 2=moderate, 3=high, 4=extreme, 5=chronic)
 *See Section VII.

164 - Cerulean Blue

Trade Name LIQUITEX Artist Oil Colors

SECTION II-A

HAZARDOUS COMPONENTS

Cerulean Blue paint contains the following mixture listed in OSHA Standard 29 CFR Section 1910.1000 for air contaminants.

Component	CAS #	Vapor Pressure mm Hg
Zinc chrome cobalt aluminate	74665-01-3	Zero at room temperature

SECTION II-B

OCCUPATIONAL EXPOSURE LIMITS

	OSHA PEL/TWA	ACGIH TLV/TWA
Cobalt Oxide	0.1 mg/m ³	0.05 mg/m ³
Chromium Oxide	0.5 mg/m ³	0.5 mg/m ³
Zinc Oxide	5 mg/m ³	10 mg/m ³
Aluminum Oxide	15 mg/m ³	10 mg/m ³

SECTION III

PHYSICAL DATA

Boiling point	: not established > 300°F	% Volatile by volume:	< 1%
Evaporation rate	: < 1 (ether = 1)	Weight per gallon	: 15 lbs.
Vapor density	: > 1 (air = 1)	Specific gravity	: 1.86 (H ₂ O = 1)

82529

SECTION IV

HEALTH INFORMATION

Eye contact: Inert, nuisance particulate dust.

Skin contact: Non-toxic.

Inhalation: Do not spray apply. Avoid breathing dusts and mists. See Sections VIII & X.

Ingestion: Harmful if swallowed. Induce vomiting and call a physician.

Signs and symptoms: No specific hazard is known.

Aggravated medical conditions: Avoid using if pregnant or contemplating pregnancy.

Other health effects: Exposure may cause nervous system, kidney, or bone marrow damage, or harm to developing fetus.

SECTION V

EMERGENCY AND FIRST AID PROCEDURES

Eye contact: Immediately flush eyes with water for at least 15 minutes. Seek medical attention if any symptoms persist.

Skin contact: Wipe excess from skin and flush with water using soap if available. Seek medical attention if irritation occurs.

Inhalation: Remove victim to fresh air and treat symptomatically. Seek medical attention.

Ingestion: Induce vomiting and call a physician.

SECTION VI

FIRE AND EXPLOSION HAZARDS

Flammability classification - OSHA: CLASS III B
- DOT: not regulated

Flash point: >300°F

Extinguishing media: Use water fog, foam, dry chemical or carbon dioxide.

Special fire fighting procedures and precautions: None known.

Unusual fire and explosion hazards: None known.

SECTION VII

REACTIVITY

Stability: Stable

Hazardous polymerization: Will not occur.

Conditions and materials to avoid: None known.

Hazardous decomposition products: Carbon dioxide, carbon monoxide and unidentified (unknown) organic compounds may be formed during combustion.

SECTION VIII

EMPLOYEE PROTECTION

Respiratory protection: Use good ventilation - For dust and mists, use NIOSH-certified mask.

Protective clothing: Avoid contact with eyes. Wear goggles if there is likelihood of contact with eyes.

Additional protective measures: Use ventilation as required to control vapor concentrations. Eye wash fountains and safety showers should be available for use in an emergency.

SECTION IX

ENVIRONMENTAL PROTECTION

Spill or leak procedures: Soak up residue with an absorbent such as clay, sand or other suitable material; place in non-leaking containers for proper disposal. Flush area with water to remove trace residue; dispose of flush solutions as above. Small spills - take up with an absorbent material and place in non-leaking containers; seal tightly for proper disposal.

Waste disposal: Refer to latest EPA or State regulations regarding proper disposal.

SECTION X

ADDITIONAL PRECAUTIONS

For Air Brushing: Use NIOSH-certified respirator. Do not inhale spray from air brush. Use window exhaust fan to remove vapors and assure adequate cross ventilation.

For Sanding Dried Paint: Use NIOSH-certified respirator. Do not inhale from sanding operation.

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of the product described herein.