

827W

Pg

PG BOX 1207
CELLUCLAY

MATERIAL SAFETY DATA SHEET (MSDS)

CELLUCLAY
5741 - all Codes
5743 - all Codes

SECTION I

EMERGENCY TELEPHONE NO.

TRADE NAME
(if None, Put Chemical) CELLUCLAY

(617) 583-0025 (DAY)

CHEMICAL NAME
AND SYNONYMS NA

MANUFACTURER'S NAME
AND TELEPHONE NO. Activa Products

(617) 583-0025

ADDRESS (Number, Street
City, State, Zip Code) P.O. Box 472

Westford MA 01886

SECTION II - HAZARDOUS INGREDIENTS

	%	TLV	PEL	UNITS
Product consists of:	100			
Gypsum		10*	15*	MG/M3
Starch		10*	15*	MG/M3
Printed clay coat sulfite paper - (as Cellulose (paper fiber))		10*	15*	MG/M3
Perlite		**	50	MPPCF
Sodium benzoate		NE	NE	
*TLV and PEL are as nuisance particulate, total dust.				
**TLV-10 mg/m3				

SECTION III - PHYSICAL DATA

BOILING POINT (°F)	NA	SPECIFIC GRAVITY (H ₂ O=1)	>60
VAPOR PRESSURE (MM Hg.)	NA	PERCENT VOLATILE BY VOLUME (%)	NA
VAPOR DENSITY (AIR=1)	NA	pH	NA
SOLUBILITY IN WATER	Appreciable	EVAPORATION RATE	NA
APPEARANCE AND ODOR Greyish powder; odorless			

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	NONE	FLAMMABLE LIMITS	LEL NE	UEL NE
EXTINGUISHING MEDIA Water				
SPECIAL FIRE FIGHTING PROCEDURES No special procedures required.				
UNUSUAL FIRE AND EXPLOSION HAZARDS Dust clouds will present a fire hazard when exposed to heat or flame.				

NA - Not Applicable

NE - Not Established

UN - Unavailable

82708

SECTION V - HEALTH HAZARD INFORMATION

SYMPTOMS/EFFECTS OF OVEREXPOSURE Inhalation of dust may cause respiratory irritation. Prolonged contact may cause mild skin irritation in sensitive individuals. Eye contact causes irritation.

FIRST AID

EYES Flush eyes with large amounts of water. Get medical attention if irritation persists.

SKIN Wash thoroughly with soap and water. Get medical attention if irritation persists.

INHALATION Move victim to fresh air. Get medical help if irritation persists.

INGESTION Contact local poison control center or physician IMMEDIATELY!

SECTION VI - REACTIVITY DATA

STABILITY Normally Stable.
Avoid heat, open flame
INCOMPATIBLE MATERIALS Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS Combustion may produce Carbon monoxide, Carbon dioxide, Sulfur dioxide

SECTION VII - SPILL OR LEAK PROCEDURES

PROCEDURES Carefully clean up spilled material and place in dry containers for reuse or disposal. Avoid excessive dust generation.

WASTE DISPOSAL METHOD Dispose of in accordance with Local, State, and Federal regulations.

SECTION VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY Not normally required. If TLV is exceeded, or for symptoms of overexposure, wear a NIOSH-approved dust/mist respirator.

EYEWEAR If potential for eye contact exists, wear chemical goggles.

CLOTHING/GLOVES Not normally required.

VENTILATION Local exhaust may be necessary under some handling/use conditions. Specific needs should be addressed by supervisory or health/safety personnel.

SECTION IX - SPECIAL PRECAUTIONS

Store in dry area. This product does not contain any carcinogens (at 0.1% or greater) as defined by IARC, NTP, or OSHA.

APPROVAL Timothy J. Calliston, CIH August 15, 1986
NAME TITLE DATE

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended as to the applicability of this information to the user's intended purpose or for the consequences of its use or misuse.