

2007

97-14310

97-14311

1439

Item # 8504  
ULANO G-SS

ULANO

MATERIAL SAFETY DATA SHEET

PRODUCT NAME  
ULANO® STA-SHARP ADHERING LIQUID UN 1993

SECTION I

Manufacturer's Name <b>ULANO CORPORATION</b>	Emergency Telephone Number <b>CHEMTREC (800)424-9300</b>
Address (Number, Street.) <b>255 BUTLER ST.</b>	Telephone Number for Information <b>(718)622-5200 Fax# (718)802-1119</b>
(City, State, ZIP Code) <b>BROOKLYN, NY. 11217</b>	Date Prepared <b>JUNE 1, 1995</b>
Signature of Preparer (optional)	

SECTION II - Ingredients/Identity Information

(Specific Chemical Identity, Common Name(s))

Ingredients	C.A.S. #	OSHA PEL	ACGIH TLV	APPROX. CONC.	HAZARD TYPE
HEPTANE	CAS# 142-82-5	400PPM	400PPM (I)	40%	FLAMMABLE
ETHYL ACETATE	CAS# 141-78-6	400PPM	400PPM	30%	FLAMMABLE
BUTYL ACETATE	CAS# 123-86-4	150PPM	150PPM	5%	FLAMMABLE
ISOPROPYL ALCOHOL	CAS# 67-63-0	400PPM	400PPM	25%	FLAMMABLE

THIS PRODUCT CONTAINS SARA TITLE III, SECTION 313 REPORTABLE CHEMICALS

ULANO PRODUCTS ARE NOT MANUFACTURED WITH, NOR DO THEY CONTAIN CLASS-I OR CLASS-II OZONE DEPLETING CHEMICALS.

SECTION III - Physical/Chemical Characteristics

Boiling Point <b>168°F</b>	Specific Gravity (H <sub>2</sub> O=1) <b>0.78</b>
Vapor Pressure (mm Hg.) <b>76</b>	Melting Point <b>N.A.</b>
Vapor Density (AIR=1) <b>HEAVIER THAN AIR</b>	Evaporation Rate (H <sub>2</sub> O=1) <b>HIGHER</b>
Solubility in Water <b>PARTIALLY SOLUBLE</b>	
Appearance and Odor <b>COLORLESS LIQUID, FRUIT-LIKE ODOR</b>	

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used) <b>40°F</b>	Flammable Limits	LEL <b>1.12%</b>	UEL <b>6.7%</b>
Extinguishing Media <b>WATER FOG, CARBON DIOXIDE OR DRY CHEMICAL</b>			
Special Fire Fighting Procedures <b>SELF-CONTAINED BREATHING APPARATUS WITH PRESSURE DEMAND OR POSITIVE PRESSURE SOURCES.</b>			
Unusual Fire and Explosion Hazards <b>VAPOR HEAVIER THAN AIR. MAY TRAVEL ALONG GROUND TO OTHER IGNITION SOURCES.</b>			

SECTION V - Reactivity Data

Stability	Unstable	Stable	<b>X</b>
Conditions to Avoid <b>IGNITION SOURCES</b>			
Incompatibility (Material to Avoid) <b>STRONG OXIDIZING AGENTS</b>			
Hazardous Decomposition or Byproducts <b>COMBUSTION CAN PRODUCE CARBON DIOXIDE AND CARBON MONOXIDE</b>			
Hazardous Polymerization	May Occur	Will Not Occur	<b>X</b>
Conditions to Avoid <b>NONE KNOWN</b>			
HMS	Health [ 2 ]	Flammability [ 3 ]	Reactivity [ 0 ]      Personal Protection [ C ]

Protective Gloves <b>SOLVENT RESISTANT RUBBER GLOVES</b>	Eye Protection <b>NIOSH APPROVED GOGGLES</b>
Other Protective Clothing or Equipment <b>IMPERVIOUS APRON</b>	
Work / Hygienic Practices <b>WORK CAREFULLY, AVOID SPILLS.</b>	

V# 088255 11/19/97

WHILE THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF ULANO CORP. MAKES NO WARRANTY WITH RESPECT THERETO AND DISCLAIMS ALL LIABILITY FROM RELIANCE THEREON.