

1062

MATERIAL SAFETY DATA SHEET

FOR COATINGS, RESINS AND RELATED MATERIALS
(Approved by US Department of Labor "Essentially Similar" to Form OSHA-201)

NPCA 1-72

DATE OF PREPARATION
OCT 08 1986 AUG 2

#85542-85544

Section 1

American Art Clay Co., Inc.
Reward Ceramic Color Mfrs., Co.
4717 W. Sixteenth Street
Indianapolis, IN 46222

EMERGENCY TELEPHONE NO.
(317) 244-6871, (800) 428-3239, (800) 358-8252.
or contact your local poison control center.
TELEX 272145 AMACO IND

PRODUCT CLASS: Semi-Moist Underglaze

TRADE NAME: AMACO

MANUFACTURERS CODE IDENTIFICATION:

Packaging: 8 Whole pans in box
8 - 1/2 oz. tubes

Semi-Moist Underglaze
Tube Underglazes

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE
		PPM	mg/M3		
Non-Toxic Bears the AP Seal Conforms to ASTM D4236 See Section V	100	NA	NA	NA	NA

85542-85544

SPECIAL LABELING INSTRUCTIONS

American Art Clay Co., Inc./Reward Ceramic Color Mfrs., Co. is a member of the Art and Craft Material Institute, 715 Boylston St., Boston MA 02116. Our art and craft materials are certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D-4236 (American Society for Testing and Materials). This product is appropriately labeled with one of the following nontoxic seals:



*Products bearing the Certified Products Seal or the AP Approved Product Seal of The Art Craft Materials Institute, Inc. are certified in a program of toxicological evaluation by a medical expert, subject to review by the Institute's Toxicological Advisory Board to contain no materials in sufficient quantities to be toxic or injurious to humans or to cause acute or chronic health problems.

In addition, products bearing the CP Seal meet specific requirements of materials, workmanship, working qualities and color described in the appropriate Product Standard issued by The Art and Craft Materials Institute, Inc. or other recognized standards organization.

Section III - PHYSICAL DATA

BOILING RANGE: NOT APPLICABLE

VAPOR DENSITY: NOT APPLICABLE, HEAVIER, LIGHTER, THAN AIR

EVAPORATION RATE: NOT APPLICABLE,
 FASTER, SLOWER, THAN ETHER

PERCENT VOLATILE BY VOLUME: 0.0

SPECIFIC GRAVITY: Less than Sp.Gr. 2

Section IV - FIRE AND EXPLOSION HAZARD DATA

DOT CATAGORY: None

FLASH POINT: NOT APPLICABLE

LEL: NA

EXTINGUISHING MEDIA: NOT APPLICABLE - no fire or explosion hazard

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE

None

SPECIAL FIRE FIGHTING PROCEDURES: NONE

None

85542-85544

2082

Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: TLV not established for whole product
Non-toxic bears AP Seal - labeling conforms to ASTM D4236

EFFECTS OF OVEREXPOSURE:

None

EMERGENCY AND FIRST AID PROCEDURES

Not applicable

Section VI - REACTIVITY DATA

STABILITY: UNSTABLE STABLE CONDITIONS TO AVOID: None

INCOMPATIBILITY (materials to avoid):

HAZARDOUS DECOMPOSITION PRODUCTS: None

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR CONDITIONS TO AVOID: None

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Clean thoroughly with paper towel and wet sponge.

WASTE DISPOSAL METHOD:

Dispose of paper towel in trash and rinse wet sponge.

Section VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION:

NA

VENTILATION:

NA

PROTECTIVE GLOVES Not needed

EYE PROTECTION Not needed

OTHER PROTECTIVE EQUIPMENT Not needed

Section IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

None

OTHER PRECAUTIONS:

None