

MATERIAL SAFETY DATA SHEET

Product Name: **Fi:X Touch Up Stik® Repair Pencil**

Issued Date: **JANUARY 3, 1994**

Page 4

88540-88551

copy

SECTION NINE SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling And Storing: Keep product containers cool, dry and away from sources of fire. Avoid high temperatures in excess of 38°C (100°F) and storage in direct sunlight.

Other Precautions: Avoid prolonged skin and eye contact. Wash with soap and water after use.

Label Precautions: Caution: Keep out of reach of children. Do not take internally.

The information contained in this document is based upon available data and believed to be accurate. However, because the information has been obtained from various sources over which Ensign-Bickford Industries, Inc. (EBI) has no control, including the manufacturer and independent laboratories, it is provided without warranty or representation that it is complete, accurate or can be relied upon. Because EBI cannot anticipate or control the many situations in which this product may be used, EBI makes no warranty that the health and safety precautions set out in this document will be proper under all conditions. It is the sole responsibility of each user of this product to determine what is appropriate for your use and to comply with the requirements of all applicable laws. This information is provided solely for health and safety purposes. Any other use of this information is expressly prohibited.

88540-88551

MATERIAL SAFETY DATA SHEET
 Product Name: **Fl:X Touch Up Stik® Repair Pencil**
 Issued Date: **JANUARY 3, 1994** 88570-88551

Manufacturer: Darworth Company
 Division Of Ensign-Bickford Industries, Inc.
 P.O. Box 639
 3 Mill Pond Lane
 Simsbury, CT 06070

HMIS

Health	0
Flammability	1
Reactivity	0
Personal Protection	0

Contact For Further Information And Emergency : (203) 843-1200 or (800) 624-7767

SECTION ONE - PRODUCT IDENTIFICATION

Product/Trade Name: **Fl:X Touch Up Stik® Repair Pencil**
 Generic Name: **Wood Repair Pencil**
 Chemical Family: **Wax Base Filler**

SECTION TWO - HAZARDOUS COMPONENTS

COMPONENTS:

Paraffin Wax

C.A.S. Number: 8002-74-2	Percentage: > 45%
T.L.V.: 2 mg/m ³ (fume)	P.E.L.: 2 mg/m ³

This Product Does Not Contain Ingredients Listed By IARC, NTP, Or OSHA As Carcinogens Or Potential Carcinogens. See Section Nine.

SECTION THREE - PHYSICAL DATA FOR CAULK

Boiling Point:	650°F
Vapor Pressure:	<0.5mm Hg @ 25°C
Vapor Density:	Negligible
Solubility In Water:	< Butyl Acetate
Evaporation Rate:	Heavier Than Air
Appearance And Odor:	Wax Stick With A Slight Wax Odor

Specific Gravity:	0.97
Percent Volatile:	N/A
Melting Point:	52°C 124°F

Post-it™ Fax Note	7671	Date	5/18	# of pages	34
To	GREG	From	PATTI		
Co./Dept	CLOVERDALE	Co.	TRE-W		
Phone #		Phone #			
Fax #	300-738-3440	Fax #			

MATERIAL SAFETY DATA SHEET

Product Name: **FI:X Touch Up Silk® Repair Pencil**
Issued Date: **JANUARY 3, 1994**
Page 2

88510-8851 ZofA

SECTION FOUR: FIRE AND EXPLOSION HAZARD DATA

Flash Point: 400°F **Flammable Limits:** LEL: N/A UEL: N/A
Hazardous Decomposition Products: Acetic Acid, Acrolein, Aldehydes, Carbon Dioxide, Carbon Monoxide Soot and Smoke.
Extinguishing Media: Foam, CO₂, Dry Chemical or Water Fog
Special Firefighting Procedures: Treat as an oil fire. Fumes, smoke and soot will be evolved. Self-contained breathing apparatus should be available for firefighters. Cool fire-exposed containers with water.
Unusual Fire And Explosion Hazards: Water may cause frothing.
Auto Ignition: N/A

SECTION FIVE: HEALTH HAZARD DATA

Permissible Exposure Limit: Refer to Section Two
Threshold Limit Value: Refer to Section Two
Effects Of Acute Overexposure to Paraffin Wax: Refer to Section Two
Eye Contact: Prolonged exposure to fumes emitted by the molten material may cause tearing. Contact with the molten material may cause thermal burns.
Skin Contact: Contact with the molten material may cause thermal burns.
Inhalation: Solid material is not volatile, so exposure by inhalation is unlikely. If working with molten material, prolonged exposure to fumes may cause irritation of nose and throat.
Ingestion: Accidental ingestion of this material may cause irritation of the digestive tract.
Effects Of Chronic Overexposure to Paraffin Wax: Refer to Section Two
Eye Contact: Repeated exposure to fumes emitted by the molten material may cause tearing. Contact with the molten material may cause thermal burns.
Skin Contact: See Acute Overexposure
Inhalation: No adverse effects are evident in the available information.
Ingestion: No adverse effects are evident in the available information.

EMERGENCY AND FIRST AID PROCEDURES

Eye Contact: Flush eyes immediately with large quantities of water for at least 15 minutes. Seek immediate medical attention if irritation develops.
Skin Contact: Remove solid product mechanically and wash with soap and water. If irritation persists, contact a physician. Note: For hot liquid product, cool immediately. If second or third degree burns are suspected, do not remove product, see physician immediately.

MATERIAL SAFETY DATA SHEET

Product Name: Fl: X Touch Up Suk® Repair Pencil

Issued Date: JANUARY 3, 1984

Page 3

88570-88551

4/8/84

Inhalation: Move to fresh air. Provide artificial respiration, if necessary. See immediate medical aid.

Ingestion: Do not induce vomiting. See physician immediately.

Medical Conditions Aggravated By Exposure:

Skin- People with pre-existing skin disorders may be more susceptible to the effects of this product.

Inhalation- People with pre-existing respiratory disorders such as asthma, may be aggravated by exposure to this material.

SECTION SIX: REACTIVE CHEMICALS

Hazardous Polymerization: Will not occur.

Stability: This product is stable in most conditions. Use this product only as recommended by manufacturer.

Incompatibility: Strong oxidizing agents, acids and alkalies.

SECTION SEVEN: SPILL OR LEAK PROCEDURES

Procedure: If cold material spilled, it may be picked up by hand and often need not be disposed of. If disposal is necessary, consult federal, state and local laws prior to disposal.

SECTION EIGHT: PROTECTIVE EQUIPMENT TO BE USED

Ventilation

Respiratory Protection: Not needed during normal use. If product is heated and if vapor concentrations exceed the TLV and PEL for paraffin wax, use a National Institute of Occupational Safety and Health approved respirator.

Local Exhaust: Not normally required.

Special: N/A

Mechanical: Not normally required.

Outdoors: N/A

Protective Clothing

Protective Gloves: Not normally required. Neoprene or rubber gloves may be necessary to avoid possible skin irritation in sensitive individuals.

Eye Protective: Not required under normal use.

Other Equipment: None