12450

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing, Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

		SECT	ION I					
MANUFACTURER'S NAME		MERGENCY TELEPHONE NC.						
				(412) 741-2010				
ADDRESS (Number, Street, City, State, and ZIP Coc Avenue B, Leetsdale, Pennsylv	<i>r</i> áni		66					
CHEMICAL NAME AND SYNONYMS						n		
CHEMICAL FAMILY			FORMULA					
SECTION II HAZARDOUS INGREDIENTS								
PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS			TLV (Units)		
PIGMENTS			BASE METAL NOT					
CATALYST NOT			ALLCYS Applicable					
VEHICLE Applicable			METALLIC COATINGS					
SOLVENTS			FILLER METAL PLUS COATING OR	CORE FLUX				
ADDITIVES			OTHERS					
OTHERS								
MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES					%	TLV (Units)		
A mixture of vegetable waxes and oils, petroleum waxes and oils,						<u> </u>		
insect wax, animal oils and greases and triarylmethane and triphenyl-								
methane dyes on a paper substrate. All materials are listed as non-								
hazardous by the manufacturers. Dyes Only, Rat LD ₅₀ @ 460 MG/KG								
SECTION III - PHYSICAL DATA								
BOILING POINT (°F.)		N/A	SPECIFIC GRAVITY (H2O+1)					
VAPOR PRESSURE (mm Hg.)		N/A	PERCENT, VOLATILE BY VOLUME (%)			one		
VAPOR DENSITY (AIR=1)		N/A	EVAPORATION RATE (one		
SOLUBILITY IN WATER	Dy	es Only						
APPEARANCE AND OOOR						. ·		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA							
FLASH POINT (Method used)	FLAMMABLE LIMITS	Lel	Uel				
EXTINGUISHING MEDIA							
SPECIAL FIRE FIGHTING PROCEDURES	Not						
	Applicable						
UNUSUAL FIRE AND EXPLOSION HAZARDS							

Y	S	ECTION V	- HEAL	TH HAZAF	RD DATA		
THRESHOLD LIMIT	VALUE : 1	None 1	Establi	shed	, ė , -		
EFFECTS OF OVER	XPOSURE				<u> </u>		
 					·		
EMERGENCY AND F	IRST AID PROCED	JRES					
							
				EACTIVITY	DATA		·
STABILITY	UNSTABLE	c	ONDITION	S TO AVOID			
	STABLE	X			·	<u> </u>	
Oxidizing ar	(Materials to avoid) d Reducing A	gents may	change	chemical	compositi	on.	
HAZARDOUS DECO Carbon	MPOSITION PRODU Oxides	стѕ					
HAZARDOUS	MAY OCCU	R		CONDITIONS	TO AVOID		
POLYMERIZATION	WILL NOT	OCCUR	X				
•				·		*!	
1	n in case mater	IAL IS RELEA	SED OR S	PILLED	ROCEDURE	Snet	:
WASTE DISPOSAL	METHOD						
		:	· .				
:	SECTION	VIII - SP	ECIAL P	ROTECTIO	N INFORMA	TION	
RESPIRATORY PRO	TECTION (Specify	ype)					
VENTILATION	LOCAL EXHAUST		Not		SPECIAL		
٠.	MECHANICAL (G	eneral)		icable	OTHER	-	
PROTECTIVE GLOV	ES			EYE PROTEC	TION		
OTHER PROTECTIV	E EQUIPMENT		·_·				
		SECTION I	X · SPE	CIAL PREC	AUTIONS		
PRECAUTIONS TO	BE TAKEN IN HAN	DLING AND S	TORING	 -			
		None Nece	essarv			<u> </u>	
OTHER PRECAUTION						<u></u>	··
			:		· · · · · · · · · · · · · · · · · · ·	·	

PAGE (2) GPO 930.540

. , .

Form OSHA-20 Rev. May 72