Material Safety Data Sheet

POWER #49145

Page 1 of 4

SOLID POWER

Section 1. Chemical product and company identification

Trade name

: SOLID POWER

Product use Supplier : Machine Warewashing Detergent: Ecolab Inc. Institutional Division

370 N. Wabasha Street St. Paul, MN 55102 1-800-352-5326

Code

: 949008

Date of issue

25-August-2008

EMERGENCY HEALTH INFORMATION: 1-800-328-0026 Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

<u>Name</u>	CAS number	% by weight
sodium hydroxide	1310-73-2	36
triphosphoric acid, pentasodium salt	7758-29-4	14
sodium carbonate	497-19-8	20 - 50

Section 3. Hazards identification

Physical state

: Solid [Cast Solid]

Emergency

WARNING!

overview

CAUSES SEVERE EYE AND SKIN IRRITATION. Untreated contact may cause severe

irritation or chemical burns.

MAY BE HARMFUL IF SWALLOWED.

May cause burns to mouth, throat and stomach.

Do not ingest. Do not get in eyes, on skin or on clothing. Wash thoroughly after handling.

Potential acute health effects

Eyes

: Severely irritating to eyes. Untreated contact may cause chemical burns.

Skin

: Severely irritating to the skin. Untreated contact may cause severe irritation or chemical

burns

Inhalation

: No known significant effects or critical hazards.

Ingestion : May be harmful if swallowed. Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

Section 4. First aid measures

Eye contact

: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and continue flushing with plenty of water for at least 15 minutes. Get medical attention

immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing

before reuse. Clean shoes thoroughly before reuse.

Inhalation

: If inhaled, remove to fresh air.

Ingestion

: If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention immediately.

SOLID POWER Page: 2/4

Section 5. Fire fighting measures

Flash point

: > 100°C

Product does not support combustion.

Hazardous thermal decomposition products

Decomposition products may include the following materials: carbon dioxide

carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides

Fire-fighting media and instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dike area of fire to prevent runoff. No specific fire or explosion hazard.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Stop leak if without risk. Use suitable protective equipment. Keep unnecessary personnel away. Do not touch or walk through spilled material.

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

: If emergency personnel are unavailable, vacuum or carefully scoop up spilled material and place in an appropriate container for disposal.

Section 7. Handling and storage

Handling Storage

: Do not ingest. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

Keep out of the reach of children. Do not allow water to enter container. Keep container tightly closed. Keep container in a cool, well-ventilated area.

Store between the following temperatures: -10 and 50°C

Section 8. Exposure controls/personal protection

Engineering measures

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Personal protection:

: Due to the form and packaging of the product, no protective equipment is needed under normal

Eyes Hands

use conditions. : Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Skin

: Due to the form and packaging of the product, no protective equipment is needed under normal use conditions.

Respiratory

: A respirator is not needed under normal and intended conditions of product use.

Exposure limits

sodium hydroxide

ACGIH TLV (United States, 1/2008). C: 2 mg/m3

OSHA PEL (United States, 11/2006).

TWA: 2 mg/m3 8 hour(s).

SOLID POWER Page: 3/4

Section 9. Physical and chemical properties

Physical state

Solid. [Cast Solid] : Blue. [Light]

Color Odor

: Faint odor.

рH Solubility : 12 to 13 [Conc. (% w/w): 1%]

: Easily soluble in the following materials: cold water and hot water.

Section 10. Stability and reactivity

Stability

The product is stable. Under normal conditions of storage and use, hazardous

polymerization will not occur.

Reactivity

Extremely reactive or incompatible with the following materials: acids. Highly reactive or incompatible with the following materials: metals.

Reactive or incompatible with the following materials: organic materials and moisture. Hazardous decomposition : Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

products Hazardous polymerization

: Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Potential acute health effects

Eyes

: Severely irritating to eyes. Untreated contact may cause chemical burns,

Skin

Severely irritating to the skin. Untreated contact may cause severe irritation or chemical

Inhalation

: No known significant effects or critical hazards.

Ingestion

: May be harmful if swallowed. Causes burns to mouth, throat and stomach.

Potential chronic health effects

Target organs

: Contains material which may cause damage to the following organs: lungs, upper respiratory tract.

Section 12. Ecological information

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN Classification

UN number

UN1759

Proper shipping name

CORROSIVE SOLIDS, N.O.S. (Contains Sodium hydroxide)

Class

Packing group

111

See shipping documents for specific transportation information.

SOLID POWER

#49145

Section 15. Regulatory information

HCS Classification

: Corrosive material Target organ effects

U.S. Federal regulations

: SARA 302/304/311/312 extremely hazardous substances: No products were

found

SARA 302/304 emergency planning and notification: No products were

found.

TSCA 8(b) inventory : All components are listed or exempted.

California Prop. 65

: No products were found.

Section 16. Other information

Hazardous Material

Information System (U.S.A.)

Flammability 0
Physical impersis 0

Date of issue Responsible name Date of previous issue : 25-August-2008.: Regulatory Affairs: 15-August-2005.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.