

## Krypton 222nm Ceiling Mount Luminaire

### Model # Krypton-11

### Specifications:

#### Mechanical:

**Form:** Circular

**Diameter:** 7.6" (193mm)

**Height:** 1.76" (44.7mm)

#### Electrical:

**Operating Voltage:** 12VDC +/- 1  
(optional 24VDC available)

**Input power nominal:** 10W +/- 1

**Input power Max.:** 15W

**Input Current Nominal:** .85A +/- .1

**Input Current Max.:** 1.25A

#### Optical Properties:

**Lamp life:** 3,000 hours

**Expected Luminaire life:** Up to 15 years  
(depending on operating parameters)

**200-230nm output:** 38mw (peak  
@222nm) Beam dispersion: 0-80 degrees  
(1/2 angle)

#### Operation and Storage:

**Operating Temperature range:** -20 to 60C

**Operating humidity:** 10-80%

**Altitude:** 0-10,000 ft.

**Storage humidity:** < 90%

**Storage temperature:** <60C

#### Design Parameters:

- Up to 3 log+ (99.9%) cumulative disinfection per day
- Designed to meet and not exceed IEC/EN 62471 and ACGIH 222nm UV exposure Threshold Limit Values (TLV) for human exposure
- Air and surface disinfection for up to 250 square feet per fixture with 8-11 ft ceiling
- No degradation in output over the life of the lamp
- Environmentally friendly/mercury free
- Instant on/off
- Delivered dosage is not impacted by ambient temperature



#### Included Accessories:

- 100-277VAC 50/60hz to 12VDC 60W transformer
- Drop ceiling clip mount
- Ceiling mounting plate and hardware for 1/4 twist lock installation
- 20 feet 2 conductor shielded cable
- Installation manual

**ISO9001 Certified**

**EPA company #: 96253**

**Made in the U.S.A.** 