

Version 3.0

REVISION DATE: 07/08/2012

Print Date 07/18/2015

#### **SECTION 1 - PRODUCT IDENTIFICATION**

Trade name

BURMASTIC GLAS PLY 2 SQ./33 LB T2GBBURMASTIC GLAS PLY 2 SQ./33

LB T2GB

Product code

: 008155B601

COMPANY

Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone

(216) 292-5000 8:30 - 5:00 EST

Emergency Phone:

(216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use

: Roof Sheeting

## **SECTION 2 - HAZARDS IDENTIFICATION**

#### **Emergency Overview**

Black. Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

## Acute Potential Health Effects/ Routes of Entry

Inhalation

Not applicable under normal conditions of use.

Eyes Ingestion Not applicable under normal conditions of use. Not applicable under normal conditions of use.

Skin

May cause mild irritation.

#### **Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

#### **Chronic Health Effects**

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation.

Target Organs: Skin, Eye, Lung

#### **SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Oxidized asphalt	64742-93-4	40.0 - 70.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	40.0 - 70.0

An RPM Company

1/6



Version 3.0

REVISION DATE: 07/08/2012

Print Date 07/18/2015

Fibrous Glass

65997-17-3

7.0 - 13.0

## **SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation

: Generally not required under normal conditions of use.

Eye contact

Generally not required under normal conditions of use.

Skin contact

Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion

Not applicable under normal conditions of use.

Notes to physician

: Not applicable.

#### SECTION 5 - FIRE FIGHTING MEASURES

Flash point

Not available.

Method

Not available. Not available.

Lower explosion limit

Upper explosion limit

Not available.

Autoignition temperature Hazardous combustion

Not available.

products

firefighters

Hydrogen sulfide and hydrocarbon fractions.

Protective equipment for

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

## **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Scrape up and transfer to appropriate container for disposal.

#### SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions.

#### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

# Personal protection equipment

Respiratory protection

: Not required under normal conditions of use.

Hand protection

Use suitable impervious leather gloves and protective apparel to reduce

exposure.

Eye protection

Wear appropriate eye protection.

Skin and body protection

Not required.

Protective measures

Other equipment not normally required.

Engineering measures

General ventilation is sufficient.

RPM company 2/6



Version 3.0

REVISION DATE: 07/08/2012

Print Date 07/18/2015

#### **Exposure Limits**

CAS Number	Regulation	Limit	<u>Form</u>
14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
	OSHA TWA:	0.3 mg/m3	Total dust.
	OSHA PEL:	15 mg/m3	Total dust.
	OSHA PEL:	5 mg/m3	Respirable fraction.
	ACGIH TWA:	0.025 mg/m3	Respirable fraction.
65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
	14808-60-7	14808-60-7 OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	14808-60-7 OSHA TWA: 0.1 mg/m3 OSHA TWA: 0.3 mg/m3 OSHA PEL: 15 mg/m3 OSHA PEL: 5 mg/m3 ACGIH TWA: 0.025 mg/m3

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form

Solid ply rolls

Color

: Black

Odor

: Asphalt

pΗ

: Not available.

Vapour pressure

Not available.

Vapor density

: Not available.

Melting point/range

: > 200 °F, > 93 °C

Freezing point

: Not available.

Boiling point/range

: > 700 °F, > 371 °C

Water solubility

: Not available.

Specific Gravity

: 1.0

% Volatile Weight

: 0%

## **SECTION 10 - REACTIVITY / STABILITY**

Stability

Material is stable under normal storage, handling, and use.

Hazardous polymerization

: Will not occur.

#### SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available



Version 3.0

REVISION DATE: 07/08/2012

Print Date 07/18/2015

#### **SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method

As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

## SECTION 14 - TRANSPORTATION / SHIPPING DATA

#### CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

#### **SECTION 15 - REGULATORY INFORMATION**

#### North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components

None present or none present in regulated quantities.

SARA 311/312 Hazards

: Acute Health Hazard Chronic Health Hazard

OSHA Hazardous Components:

Crystalline Silica (Quartz)/ Silica Sand

14808-60-7

Fibrous Glass

65997-17-3

OSHA Status: Considered

: Irritant

An RPM Company 4/6



Version 3.0

Print Date 07/18/2015

**REVISION DATE: 07/08/2012** 

hazardous based on the

Carcinogen

following criteria:

OSHA Flammability

Not Regulated

Regulatory VOC (less water and

: 0 g/l

exempt solvent)

VOC Method 310

: 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand

14808-60-7

Fibrous Glass

65997-17-3

U.S. State Regulations:

MASS RTK Components ? Crystalline Silica (Quartz)/ Silica Sand

14808-60-7

Fibrous Glass

65997-17-3

Penn RTK Components

: Oxidized asphalt

64742-93-4

Crystalline Silica (Quartz)/ Silica Sand

14808-60-7

Fibrous Glass

65997-17-3

NJ RTK Components

Oxidized asphalt

64742-93-4

Crystalline Silica (Quartz)/ Silica Sand

14808-60-7

Fibrous Glass

65997-17-3

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

# SECTION 16 - OTHER INFORMATION

#### HMIS Rating:

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

#### Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

# Prepared by: Rich Mikol

## Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and

Liability Act

**DOT - Department of Transportation** 

DSL - Domestic Substance List

EPA - Environmental Protection Agency

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

RPM company 5/6

# Material Safety Data Sheet



# BURMASTIC GLAS PLY 2 SQ./33 LB T2GBBURMASTIC GLAS PLY 2 SQ./33 LB T2GB

Version 3.0

**REVISION DATE: 07/08/2012** 

Print Date 07/18/2015

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatlle Organic Compound

WHMIS - Workplace Hazardous Materials Information

Syster