

Version 2.

REVISION DATE: 05/26/2011

Print Date 06/02/2011

#### SECTION 1 - PRODUCT IDENTIFICATION

Trade name

: POWERPLY IV PLY 20 ROLLS/PALLET TPP4POWERPLY IV PLY 20

**ROLLS/PALLET TPP4** 

Product code

: 014204 503

COMPANY

: Tremco Incorporated

3735 Green Road

Cleveland, OH 44122

Telephone
Emergency Phone:

: (216) 292-5000 8:30 - 5:00 EST : (216) 765-6727 8:30 - 5:00 EST

After Hours: Chemtrec 1-800-424-9300

Product use

: Roof Sheeting

# **SECTION 2 - HAZARDS IDENTIFICATION**

# **Emergency Overview**

Black. Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

# Acute Potential Health Effects/ Routes of Entry

Inhalation

Not applicable under normal conditions of use. Not applicable under normal conditions of use.

Eyes Ingestion

Not applicable under normal conditions of use.

Skin

May cause mild irritation.

# **Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

# Chronic Health Effects

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation. Prolonged and repeated exposure to excessive airborne concentrations of taic can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung

# SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Asphalt	8052-42-4	> 60.0	
Fibrous Glass	65997-17-3	15.0 - 40.0	
Talc	14807-96-6	7.0 - 13.0	
An RPM Company	1/5	014204 503	



Version 2.

**REVISION DATE: 05/26/2011** 

Print Date 06/02/2011

#### **SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation

: Generally not required under normal conditions of use.

Eye contact

: Generally not required under normal conditions of use.

Skin contact

: Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion

: Not applicable under normal conditions of use.

Notes to physician

: Not applicable.

#### SECTION 5 - FIRE FIGHTING MEASURES

Flash point

Not available.

Method

Not available.

Lower explosion limit

Not available.

Upper explosion limit

Not available.

Autoignition temperature

Not available.

Hazardous combustion

ivoi avallable.

products

Hydrogen sulfide and hydrocarbon fractions.

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Scrape up and transfer to appropriate container for disposal.

#### SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions.

#### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Personal protection equipment

Respiratory protection

Not required under normal conditions of use.

Hand protection

Use suitable impervious leather gloves and protective apparel to reduce

exposure.

Eye protection

Wear appropriate eye protection.

Skin and body protection

Not required.

Protective measures

Other equipment not normally required.

Engineering measures

General ventilation is sufficient.

An RPM Company

2/5

014204 503



Version 2.

**REVISION DATE: 05/26/2011** 

Print Date 06/02/2011

#### **Exposure Limits**

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Talc	14807-96-6	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid ply rolls

Color

: Black

Odor

: None

рH

: Not available.

Vapour pressure

: Not available.

Vapor density

: Not available.

Melting point/range

: Not available.

Freezing point

: Not available.

Boiling point/range

Not available.Not available.

Water solubility Specific Gravity

.

Opcomo Gravity

1.0

% Volatile Weight

: 0%

#### **SECTION 10 - REACTIVITY / STABILITY**

Stability

: Material is stable under normal storage, handling, and use.

Hazardous polymerization

: Will not occur.

# **SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available



Version 2.

**REVISION DATE: 05/26/2011** 

Print Date 06/02/2011

#### **SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method

: As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

# SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:

**NOT REGULATED** 

### **SECTION 15 - REGULATORY INFORMATION**

#### North American Inventories:

All components are listed or exempt from the TSCA inventory. This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components

: None present or none present in regulated quantities.

SARA 311/312 Hazards

: Acute Health Hazard

OSHA Hazardous Components:

Asphait

8052-42-4 65997-17-3

Fibrous Glass

Talc

14807-96-6

OSHA Status: Considered hazardous based on the

: Irritant

following criteria:

OSHA Flammability

: Not Regulated

Regulatory VOC (less water and

: 0 g/l

exempt solvent)

VOC Method 310

: 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: 65997-17-3 Fibrous Glass



Version 2.

**REVISION DATE: 05/26/2011** 

Print Date 06/02/2011

#### U.S. State Regulations:

MASS RTK Components

Asphalt

Fibrous Glass

8052-42-4 65997-17-3

Taic

14807-96-6

Penn RTK Components

Asphalt

8052-42-4

Fibrous Glass

65997-17-3

Talc

14807-96-6

NJ RTK Components :

get a galanga sayar dan sali c

Asphalt

8052-42-4

Fibrous Glass

65997-17-3

Talo

14807-96-6

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

#### SECTION 16 - OTHER INFORMATION

#### **HMIS Rating:**

Health	1	
Flammability	0	
Reactivity	0	
PPE		

0 = Minimum

1 = Slight

2 = Moderate

3 = Serious

4 = Severe

### **Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

#### Prepared by: Rich Mikol

#### Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System