



**TREMFLASH TAPE 1/8" X 1" 600FT/CSTREMFLASH TAPE 1/8" X 1" 600FT/CS**

Version 1.1  
 REVISION DATE: 09/01/2006

Print Date 05/08/2009

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : TREMFLASH TAPE 1/8" X 1" 600FT/CSTREMFLASH TAPE 1/8" X 1" 600FT/CS  
 Product code : 046917 660  
 COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122  
 Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300  
 Product use : Tape

RECEIVED K.C.D.A.  
 09 MAY 15 PM 2:07

**SECTION 2 - HAZARDS IDENTIFICATION**

**Emergency Overview**

Tan. Solid. No serious effects anticipated under normal conditions of use. Generally not required under normal conditions of use.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : No serious effects anticipated under normal conditions of use.  
 Eyes : Not applicable under normal conditions of use. Direct contact may cause temporary redness and discomfort.  
 Ingestion : No known adverse effects.  
 Skin : No effects anticipated.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Calcium Carbonate (Limestone)	1317-65-3	> 60.0
Polybutene	9003-29-6	15.0 - 40.0
Polyisobutylene resin	NJ TSRN# 51721300-5362P	7.0 - 13.0
Heavy paraffinic distillate	64741-88-4	3.0 - 7.0
Hydrocarbon resin	68131-77-1	1.0 - 5.0
Amorphous silica	7631-86-9	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	< 1.0



**TREMFLASH TAPE 1/8" X 1" 600FT/CSTREMFLASH TAPE 1/8" X 1" 600FT/CS**

Version 1.1

Print Date 05/08/2009

REVISION DATE: 09/01/2006

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Generally not required under normal conditions of use.
- Eye contact : Generally not required under normal conditions of use.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Get medical attention. Do not induce vomiting.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Generally not required under normal conditions of use. Use safety glasses if eye contact is likely.

**TREMFLASH TAPE 1/8" X 1" 600FT/CS** **TREMFLASH TAPE 1/8" X 1" 600FT/CS**

Version 1.1

Print Date 05/08/2009

REVISION DATE: 09/01/2006

- Skin and body protection : Not required.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.
- Engineering measures : Not required under normal conditions of use. Use only in well ventilated areas. Provide maximum ventilation in enclosed areas.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Amorphous silica	7631-86-9	ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA TWA:	0.8 mg/m3	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	ACGIH TWA:	0.05 mg/m3	Respirable fraction.
		OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Solid
- Color : Tan
- Odor : Negligible
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Insoluble
- Specific Gravity : 1.65
- % Volatile Weight : 4 %

**TREMFLASH TAPE 1/8" X 1" 600FT/CS**Version 1.1  
REVISION DATE: 09/01/2006

Print Date 05/08/2009

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Oxidizing agents.  
 Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Amorphous silica, CAS-No.: 7631-86-9  
 Acute oral toxicity (LD-50 oral) 22,500 mg/kg (Rat)

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**  
 NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION****North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.  
 SARA 311/312 Hazards : Acute Health Hazard  
 Chronic Health Hazard

**OSHA Hazardous Components :**

Calcium Carbonate (Limestone) 1317-65-3  
 Amorphous silica 7631-86-9  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

OSHA Status: Considered : Irritant  
 hazardous based on the Carcinogen

**TREMFLASH TAPE 1/8" X 1" 600FT/CS** **TREMFLASH TAPE 1/8" X 1" 600FT/CS**

Version 1.1

Print Date 05/08/2009

REVISION DATE: 09/01/2006

following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and exempt solvent) : 78 g/l

VOC Method 310 : 4 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**U.S. State Regulations:**

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
Amorphous silica 7631-86-9

Penn RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
Polybutene 9003-29-6  
Polyisobutylene resin NJ TSRN# 51721300-5362P  
Heavy paraffinic distillate 64741-88-4  
Amorphous silica 7631-86-9

NJ RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
Polybutene 9003-29-6  
Polyisobutylene resin NJ TSRN# 51721300-5362P  
Heavy paraffinic distillate 64741-88-4  
Hydrocarbon resin 68131-77-1  
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:  
14808-60-7 Crystalline Silica (Quartz)/ Silica Sand

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	1
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

PEL - Permissible Exposure Limit  
RCRA - Resource Conservation and Recovery Act



**TREMFLASH TAPE 1/8" X 1" 600FT/CS** **TREMFLASH TAPE 1/8" X 1" 600FT/CS**

Version 1.1

Print Date 05/08/2009

REVISION DATE: 09/01/2006

DOT - Department of Transportation  
DSL - Domestic Substance List  
EPA - Environmental Protection Agency  
HMIS - Hazardous Materials Information System  
IARC - International Agency for Research on Cancer  
MSHA - Mine Safety Health Administration  
NDSL - Non-Domestic Substance List  
NIOSH - National Institute for Occupational Safety and Health  
NTP - National Toxicology Program  
OSHA - Occupational Safety and Health Administration

RTK - Right To Know  
SARA - Superfund Amendments and Reauthorization Act  
STEL - Short Term Exposure Limit  
TLV - Threshold Limit Value  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average  
V - Volume  
VOC - Volatile Organic Compound  
WHMIS - Workplace Hazardous Materials Information System