

Version 3.0

REVISION DATE: 07/08/2012

Print Date 06/17/2014

()

SECTION 1 - PRODUCT IDENTIFICATION

Trade name

: THERMGLASS TYPE IV 5 SQ. 25RL PLT TG4THERMGLASS TYPE IV 5 SQ.

25RL PLT TG4

Product code

: 14118 503M

COMPANY

: Tremco Incorporated 3735 Green Road

Cieveland, OH 44122

Telephone

: (216) 292-5000 8:30 - 5:00 EST : (216) 765-6727 8:30 - 5:00 EST

Emergency Phone:

After Hours: Chemtrec 1-800-424-9300

Product use

: Roof Sheeting

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Black. Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation Eyes Not applicable under normal conditions of use. Not applicable under normal conditions of use. Not applicable under normal conditions of use.

Ingestion Skin

May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation. Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %	
Asphalt	8052-42-4	> 60.0	
Fibrous Glass	65997-17-3	15.0 ~ 40.0	
Talc	14807-96-6	7.0 - 13.0	
An (27) Company 1/6 14118 5	03M		



Version 3.0

REVISION DATE: 07/08/2012

Print Date 06/17/2014

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation

: Generally not required under normal conditions of use.

Eye contact

Generally not required under normal conditions of use.

Skin contact

Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion

Not applicable under normal conditions of use.

Notes to physician

Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point

Not available.

Method

Not available. Not available.

Lower explosion limit Upper explosion limit

Not available.

Autoignition temperature

Hazardous combustion

Not available.

products

Hydrogen sulfide and hydrocarbon fractions.

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

Respiratory protection

: Not required under normal conditions of use.

Hand protection

: Use suitable impervious leather gloves and protective apparel to reduce

exposure.

Eye protection

: Wear appropriate eye protection.

Skin and body protection

: Not required.

Protective measures

: Other equipment not normally required.

Engineering measures

General ventilation is sufficient.

RPIT Company

2/6

14118 503M



Version 3.0

REVISION DATE: 07/08/2012

Print Date 06/17/2014

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Talc	14807-96-6	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid ply rolls

Color

: Black

Odor

: None

pΗ

: Not available.

Vapour pressure

: Not available.

Vapor density

: Not available.

Melting point/range

: Not available.

Freezing point

: Not available.

Boiling point/range

: Not available.

Water solubility

: Not available.

Specific Gravity

: 1.0

% Volatile Weight

: 0%

SECTION 10 - REACTIVITY / STABILITY

Stability

: Material is stable under normal storage, handling, and use.

Hazardous polymerization

: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available



Version 3.0

REVISION DATE: 07/08/2012

Print Date 06/17/2014

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method

: As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components

None present or none present in regulated quantities.

SARA 311/312 Hazards

: Acute Health Hazard

OSHA Hazardous Components:

Asphalt

8052-42-4

Fibrous Glass

65997-17-3

Talc

14807-96-6

OSHA Status: Considered

: Irritant

An PPTT Company 4/6 14118 503M



Version 3.0

Print Date 06/17/2014

REVISION DATE: 07/08/2012

hazardous based on the following criteria:

OSHA Flammability

: Not Regulated

Regulatory VOC (less water and

: 0 g/l

exempt solvent)

VOC Method 310

: 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Fibrous Glass

65997-17-3

U.S. State Regulations:

MASS RTK Components

Asphalt

8052-42-4

Fibrous Glass

65997-17-3

Talc

14807-96-6

Penn RTK Components

NJ RTK Components

Asphalt

8052-42-4

Fibrous Glass

65997-17-3

Talc

14807-96-6

iaic

8052-42-4

Asphalt Fibrous Glass

65997-17-3

Talc

14807-96-6

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum	
Flammability	0	1 = Slight	
Reactivity	0	2 = Moderate	
PPE		3 = Serious	
		4 = Severe	

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists CERCLA - Comprehensive Environmental Response, Compensation, and

Liability Act
DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

An **RPITI** Company 5/6 14118 503M



Version 3.0

REVISION DATE: 07/08/2012

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

Print Date 06/17/2014

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System