

Version 2.0

REVISION DATE: 07/08/2012

Print Date 07/31/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name

POWERPLY VI PLY 20 ROLLS PALLET TPP6POWERPLY VI PLY 20

ROLLS PALLET TPP6

Product code

14206 503

COMPANY

: Tremco Incorporated 3735 Green Road

Cleveland, OH 44122

Telephone

: (216) 292-5000 8:30 - 5:00 EST : (216) 765-6727 8:30 - 5:00 EST

: (216) 765-6727 8:30 - 5:00 EST After Hours: Chemtrec 1-800-424-9300

Product use

Emergency Phone:

: Roof Sheeting

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Black. Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation

Eyes

Not applicable under normal conditions of use. Not applicable under normal conditions of use. Not applicable under normal conditions of use.

Ingestion Skin

: May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. The International Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation. Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening).

Target Organs: Skin, Eye, Lung

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Asphalt	8052-42-4	> 60.0
Fibrous Glass	65997-17-3	15.0 - 40.0
Talc	14807-96-6	5.0 - 10.0

An **RPM** Company 1/6 14206 503



Version 2.0

REVISION DATE: 07/08/2012

Print Date 07/31/2012

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation

: Generally not required under normal conditions of use.

Eye contact

Generally not required under normal conditions of use.

Skin contact

Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion

Not applicable under normal conditions of use.

Notes to physician

: Not applicable.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point

Not available.

Method

Not available. Not available.

Lower explosion limit

Not available.

Upper explosion limit

Autoignition temperature Hazardous combustion

Not available.

Hydrogen sulfide and hydrocarbon fractions.

products

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Scrape up and transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

Respiratory protection

Not required under normal conditions of use.

Hand protection

Use suitable impervious leather gloves and protective apparel to reduce

exposure.

Eye protection

Wear appropriate eye protection.

Skin and body protection

Not required.

Protective measures

Other equipment not normally required.

Engineering measures

General ventilation is sufficient.

un RPM Company

2/6



Version 2.0

REVISION DATE: 07/08/2012

Print Date 07/31/2012

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Talc	14807-96-6	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form

: Solid ply rolls

Color

: Black

Odor

: None

pН

: Not available.

Vapour pressure

: Not available.: Not available.

Vapor density

Melting point/range

: Not available.

Freezing point

: Not available.

Boiling point/range

: Not available.

Water solubility

: Not available.

Specific Gravity

: 1.1

% Volatile Weight

: 0%

SECTION 10 - REACTIVITY / STABILITY

Stability

: Material is stable under normal storage, handling, and use.

Hazardous polymerization

: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

No Data Available

Ari RPM Company

3/6



Version 2.0

REVISION DATE: 07/08/2012

Print Date 07/31/2012

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method

As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components

None present or none present in regulated quantities.

SARA 311/312 Hazards

: Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components:

Asphalt

8052-42-4

Fibrous Glass

65997-17-3

Talc

14807-96-6

An RPM Company 4/6



Version 2.0 REVISION DATE: 07/08/2012 Print Date 07/31/2012

OSHA Status: Considered

OSHA Status: Considered hazardous based on the : Irritant Carcinogen

following criteria:

OSHA Flammability

: Not Regulated

Regulatory VOC (less water and

: 0 g/l

exempt solvent)

VOC Method 310

: 0%

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen: Fibrous Glass 65997-17-3

U.S. State Regulations:

MASS RTK Components : Aspl

Asphalt 8052-42-4

Fibrous Glass 65997-17-3 Talc 14807-96-6

Penn RTK Components : Asphalt

Asphalt 8052-42-4
Fibrous Glass 65997-17-3

Talc

14807-96-6

NJ RTK Components : .

Asphalt 8052-42-4
Fibrous Glass 65997-17-3
Talc 14807-96-6

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

An RPM Company

5/6



Version 2.0

REVISION DATE: 07/08/2012

Print Date 07/31/2012

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System