

**REGLET JOINT SEALANTREGLET JOINT SEALANT**

Version 2.

Print Date 10/15/2008

REVISION DATE: 08/08/2008

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : REGLET JOINT SEALANTREGLET JOINT SEALANT  
 Product code : 367400 323

COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

Product use : Coating

**SECTION 2 - HAZARDS IDENTIFICATION****Emergency Overview**

Black / Brown. Semi-Solid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Aromatic tar contains polycyclic aromatic hydrocarbons, some of which have been shown to cause skin cancer following prolonged and repeated skin contact. Should be considered potentially carcinogenic by inhalation. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Di(2-ethylhexyl) phthalate, (dioctyl phthalate) given in the diet, produced increased incidence of liver cancers in female rats and male and female mice. An increased incidence of liver cancers or neoplasms were observed in male rats. A long-term NTP study showed that oral exposure to toluene diisocyanate (TDI) caused cancer in rats and mice. A lifetime inhalation study sponsored by the International Isocyanate Institute did not show carcinogenic activity in rats. May cause allergic skin and respiratory sensitization.

**Target Organs:** Eye, Lung, Liver, Kidney, Skin, Nerve

**REGLET JOINT SEALANT REGLET JOINT SEALANT**

Version 2.

Print Date 10/15/2008

REVISION DATE: 08/08/2008

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Aromatic process oil	64742-90-1	30.0 - 60.0
Polyurethane Polymer	NJ TSRN# 51721300-5024P	30.0 - 60.0
Calcium Carbonate (Limestone)	1317-65-3	10.0 - 30.0
Carbon Black	1333-86-4	7.0 - 13.0
Calcium oxide	1305-78-8	3.0 - 7.0
Anthracene	120-12-7	1.0 - 5.0
Dioctyl phthalate	117-81-7	<1.0
2,4-Toluene diisocyanate	584-84-9	<1.0
Toluene-2,6-Diisocyanate	91-08-7	<0.1
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	<0.1

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash-point : Not available.
- Method : Not applicable.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback.

**REGLET JOINT SEALANT**

Version 2.

Print Date 10/15/2008

REVISION DATE: 08/08/2008

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store under dry warehouse conditions away from heat and all ignition sources.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator (TC19C or equivalent) for isocyanates.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Carbon Black	1333-86-4	ACGIH TWA:	3.5 mg/m3	
		OSHA PEL:	3.5 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.

**REGLET JOINT SEALANT REGLET JOINT SEALANT**

Version 2.

Print Date 10/15/2008

REVISION DATE: 08/08/2008

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium oxide	1305-78-8	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	2 mg/m3 5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Diocetyl phthalate	117-81-7	ACGIH TWA: OSHA PEL:	5 mg/m3 5 mg/m3	
2,4-Toluene diisocyanate	584-84-9	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	
Toluene-2,6-Diisocyanate	91-08-7	ACGIH TWA: ACGIH STEL:	0.005 ppm 0.02 ppm	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL: ACGIH TWA:	0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3 0.025 mg/m3	Respirable. Total dust. Total dust. Respirable fraction. Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form : Semi-Solid  
 Color : Black / Brown  
 Odor : Solvent odor  
 pH : Not available.  
 Vapour pressure : Not available.  
 Vapor density : Heavier than air  
 Melting point/range : Not available.  
 Freezing point : Not available.  
 Boiling point/range : Not available.  
 Water solubility : Negligible  
 Specific Gravity : 1.09  
 % Volatile Weight : 4 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Strong acids.Strong bases.Amines.Water or moisture.Alcohols.  
 Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Diocetyl phthalate, CAS-No.: 117-81-7

**REGLET JOINT SEALANT REGLET JOINT SEALANT**

Version 2.

Print Date 10/15/2008

REVISION DATE: 08/08/2008

Acute oral toxicity (LD-50 oral) 25,000 mg/kg ( Rat ) 30,000 mg/kg ( Mouse ) 33,900 mg/kg ( Rabbit ) 26,300 mg/kg ( Guinea pig )  
 Acute dermal toxicity (LD-50 dermal) 10,000 mg/kg ( Guinea pig ) 25,000 mg/kg ( Rabbit )

2,4-Toluene diisocyanate, CAS-No.: 584-84-9

Acute oral toxicity (LD-50 oral) 5,800 mg/kg ( Rat )  
 Acute inhalation toxicity (LC-50) 14 mg/l for 4 h ( Rat ) 10 mg/l for 4 h ( Mouse ) 13 mg/l for 4 h ( Guinea pig ) 11 mg/l for 4 h ( Rabbit )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

TDG / DOT Shipping Description:  
 NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : Anthracene 120-12-7  
 Dioctyl phthalate 117-81-7  
 2,4-Toluene diisocyanate 584-84-9

SARA 311/312 Hazards : Acute Health Hazard  
 Chronic Health Hazard

**OSHA Hazardous Components :**

Aromatic process oil 64742-90-1  
 Calcium Carbonate (Limestone) 1317-65-3  
 Carbon Black 1333-86-4  
 Calcium oxide 1305-78-8  
 Anthracene 120-12-7  
 Dioctyl phthalate 117-81-7  
 2,4-Toluene diisocyanate 584-84-9  
 Toluene-2,6-Diisocyanate 91-08-7  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

**REGLET JOINT SEALANT REGLET JOINT SEALANT**

Version 2.

Print Date 10/15/2008

REVISION DATE: 08/08/2008

OSHA Status: Considered : Irritant  
 hazardous based on the Sensitizer  
 following criteria: Carcinogen

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 53 g/l  
 exempt solvent)

VOC Method 310 : 4 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:  
 Carbon Black 1333-86-4

**U.S. State Regulations:**

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3  
 Carbon Black 1333-86-4  
 Calcium oxide 1305-78-8  
 Anthracene 120-12-7  
 2,4-Toluene diisocyanate 584-84-9  
 Toluene-2,6-Diisocyanate 91-08-7  
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Penn RTK Components : Aromatic process oil 64742-90-1  
 Polyurethane Polymer NJ TSRN# 51721300-5024P  
 Calcium Carbonate (Limestone) 1317-65-3  
 Carbon Black 1333-86-4  
 Calcium oxide 1305-78-8  
 Anthracene 120-12-7  
 2,4-Toluene diisocyanate 584-84-9

NJ RTK Components : Aromatic process oil 64742-90-1  
 Polyurethane Polymer NJ TSRN# 51721300-5024P  
 Calcium Carbonate (Limestone) 1317-65-3  
 Carbon Black 1333-86-4  
 Calcium oxide 1305-78-8

**WARNING!** Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

64742-90-1 Aromatic process oil  
 1333-86-4 Carbon Black  
 117-81-7 Dioctyl phthalate  
 584-84-9 2,4-Toluene diisocyanate  
 91-08-7 Toluene-2,6-Diisocyanate  
 14808-60-7 Crystalline Silica (Quartz)/ Silica Sand



**REGLET JOINT SEALANT**

Version 2.  
REVISION DATE: 08/08/2008

Print Date 10/15/2008

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	1
Reactivity	1
PPE	

0 = Minimum  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

ACGIH - American Conference of Governmental Hygienists  
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT - Department of Transportation  
 DSL - Domestic Substance List  
 EPA - Environmental Protection Agency  
 HMIS - Hazardous Materials Information System  
 IARC - International Agency for Research on Cancer  
 MSHA - Mine Safety Health Administration  
 NDSL - Non-Domestic Substance List  
 NIOSH - National Institute for Occupational Safety and Health  
 NTP - National Toxicology Program  
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit  
 RCRA - Resource Conservation and Recovery Act  
 RTK - Right To Know  
 SARA - Superfund Amendments and Reauthorization Act  
 STEL - Short Term Exposure Limit  
 TLV - Threshold Limit Value  
 TSCA - Toxic Substances Control Act  
 TWA - Time Weighted Average  
 V - Volume  
 VOC - Volatile Organic Compound  
 WHMIS - Workplace Hazardous Materials Information System