



**POWERPLY STANDARD PLUS FR- WHITE GRANULE POWERPLY STANDARD PLUS FR- WHITE GRANULE**

Version 3.0

Print Date 10/01/2013

REVISION DATE: 07/08/2012

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : POWERPLY STANDARD PLUS FR- WHITE GRANULE POWERPLY STANDARD PLUS FR- WHITE GRANULE  
 Product code : 36STDPLFR601  
 COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122  
 Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300  
 Product use : Roof Sheeting

RECEIVED 10/01/13 13 OCT - 9 AM '13

**SECTION 2 - HAZARDS IDENTIFICATION**

Emergency Overview

Various colors. Solid ply rolls. Not applicable under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation : Not applicable under normal conditions of use.  
 Eyes : Not applicable under normal conditions of use.  
 Ingestion : Not applicable under normal conditions of use.  
 Skin : May cause mild irritation.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

This product contains granular materials which may cause mechanical skin, eye or respiratory irritation. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). The international Agency for Research on Cancer (IARC) has classified ceramic fiber, fibrous glasswool, and mineral wool (rockwool and slagwool) as possible human carcinogens (Group 2B) based on sufficient evidence of carcinogenicity in animals but insufficient data in humans. In the National Toxicology Program's (NTP) 7th Annual Report on Carcinogens (1994), respirable glasswool was classified as reasonably anticipated to be carcinogenic. Repeated and prolonged exposures to trivalent chromium compounds may cause delayed effects involving the respiratory system. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. OSHA considers fibrous glass dust a nuisance dust. Fibrous glass can cause dermatitis, local irritation.

Target Organs: Skin, Eye, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
An RPM Company 1/6	36STDPLFR601	



**POWERPLY STANDARD PLUS FR- WHITE GRANULE POWERPLY STANDARD PLUS FR- WHITE GRANULE**

Version 3.0

Print Date 10/01/2013

REVISION DATE: 07/08/2012

Asphalt	8052-42-4	30.0 - 60.0
Rhyolitic argillite/roofing granules	NJ TSRN# 51721300-5488P	15.0 - 40.0
Fire retardant	NJ TSRN# 51721300-5035P	15.0 - 40.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15.0 - 40.0
Styrene-butadiene copolymers	NJ TSRN# 51721300-5132P	5.0 - 10.0
Fibrous Glass	65997-17-3	1.0 - 5.0
Clay	1332-58-7	1.0 - 5.0
Carbon Black	1333-86-4	<1.0
Chromium oxide	1308-38-9	<1.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Generally not required under normal conditions of use.
- Eye contact : Generally not required under normal conditions of use.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Not applicable under normal conditions of use.
- Notes to physician : Not applicable.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not available.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Hazardous combustion products : Hydrogen sulfide and hydrocarbon fractions.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Scrape up and transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Store under normal warehouse conditions.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

Personal protection equipment

**POWERPLY STANDARD PLUS FR- WHITE GRANULE POWERPLY STANDARD PLUS FR- WHITE GRANULE**

Version 3.0

Print Date 10/01/2013

REVISION DATE: 07/08/2012

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Use suitable impervious leather gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection.
- Skin and body protection : Not required.
- Protective measures : Other equipment not normally required.
- Engineering measures : General ventilation is sufficient.

**Exposure Limits**

<b>Chemical Name</b>	<b>CAS Number</b>	<b>Regulation</b>	<b>Limit</b>	<b>Form</b>
Asphalt	8052-42-4	ACGIH TWA:	0.5 mg/m3	Inhalable fraction.as
		benzene solubles		
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
Fibrous Glass	65997-17-3	ACGIH TWA:	5 mg/m3	Inhalable fraction.
Clay	1332-58-7	ACGIH TWA:	2 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
Carbon Black	1333-86-4	ACGIH TWA:	3.5 mg/m3	
		OSHA PEL:	3.5 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

- Form : Solid ply rolls
- Color : Various colors
- Odor : None
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Not available.
- Melting point/range : Not available.
- Freezing point : Not available.



**POWERPLY STANDARD PLUS FR- WHITE GRANULE POWERPLY STANDARD PLUS FR- WHITE GRANULE**

Version 3.0

Print Date 10/01/2013

REVISION DATE: 07/08/2012

Boiling point/range : Not available.  
 Water solubility : Not available.  
 Specific Gravity : 1  
 % Volatile Weight : 0 %

**SECTION 10 - REACTIVITY / STABILITY**

Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Aluminum hydroxide, CAS-No.: 21645-51-2  
 Acute oral toxicity (LD-50 oral) 5,000 mg/kg ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : As purchased, this product, when discarded, is not a listed or characteristic hazardous waste according to Federal regulations (40 CFR 261). Check local, regional, state or provincial regulations for applicable requirements for disposal. Any processing, using, alteration or chemical additions to the product, as purchased, may alter the disposal requirements. Under Federal regulations, it is the generator's responsibility to determine if a waste is a hazardous waste. Empty containers may retain product residue. Do not reuse.

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**CFR / DOT:**

Not Regulated

**TDG:**

Not Regulated

**IMDG:**

Not Regulated



**POWERPLY STANDARD PLUS FR- WHITE GRANULE POWERPLY STANDARD PLUS FR- WHITE GRANULE**

Version 3.0

Print Date 10/01/2013

REVISION DATE: 07/08/2012

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard  
Chronic Health Hazard

**OSHA Hazardous Components :**

Asphalt	8052-42-4
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Fibrous Glass	65997-17-3
Clay	1332-58-7
Carbon Black	1333-86-4
Chromium oxide	1308-38-9

OSHA Status: Considered : Irritant  
hazardous based on the Carcinogen  
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and : 0 g/l  
exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
Fibrous Glass	65997-17-3
Carbon Black	1333-86-4

**U.S. State Regulations:**

MASS RTK Components :	Asphalt	8052-42-4
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
	Fibrous Glass	65997-17-3
	Clay	1332-58-7
	Chromium oxide	1308-38-9

Penn RTK Components :	Asphalt	8052-42-4
	Rhyolitic argillite/roofing granules	NJ TSRN# 51721300-5488P
	Fire retardant	NJ TSRN# 51721300-5035P
	Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
	Styrene-butadiene copolymers	NJ TSRN# 51721300-5132P
	Fibrous Glass	65997-17-3
	Clay	1332-58-7



**POWERPLY STANDARD PLUS FR- WHITE GRANULE POWERPLY STANDARD PLUS FR- WHITE GRANULE**

Version 3.0

Print Date 10/01/2013

REVISION DATE: 07/08/2012

NJ RTK Components : Asphalt Rhyolitic argillite/roofing granules Fire retardant Crystalline Silica (Quartz)/ Silica Sand Styrene-butadiene copolymers Fibrous Glass Carbon Black	8052-42-4 NJ TSRN# 51721300-5488P NJ TSRN# 51721300-5035P 14808-60-7 NJ TSRN# 51721300-5132P 65997-17-3 1333-86-4
--	---

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	0
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- |   |   |
|---|---|
| ACGIH - American Conference of Governmental Hygienists<br>CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act<br>DOT - Department of Transportation<br>DSL - Domestic Substance List<br>EPA - Environmental Protection Agency<br>HMIS - Hazardous Materials Information System<br>IARC - International Agency for Research on Cancer<br>MSHA - Mine Safety Health Administration<br>NDSL - Non-Domestic Substance List<br>NIOSH - National Institute for Occupational Safety and Health<br>NTP - National Toxicology Program<br>OSHA - Occupational Safety and Health Administration | PEL - Permissible Exposure Limit<br>RCRA - Resource Conservation and Recovery Act<br>RTK - Right To Know<br>SARA - Superfund Amendments and Reauthorization Act<br>STEL - Short Term Exposure Limit<br>TLV - Threshold Limit Value<br>TSCA - Toxic Substances Control Act<br>TWA - Time Weighted Average<br>V - Volume<br>VOC - Volatile Organic Compound<br>WHMIS - Workplace Hazardous Materials Information System |
|---|---|