

GEOGARD LO BASE COAT 2 GALGEOGARD LO BASE COAT 2 GAL

Version 4.0

Print Date 05/30/2014

REVISION DATE: 07/08/2012

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : GEOGARD LO BASE COAT 2 GALGEOGARD LO BASE COAT 2 GAL
 Product code : 491L002C

COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300

Product use : Coating

RECEIVED KODIAK
 14 JUN -3 AM 11:01

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Gray. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.

Eyes : Vapor and/or mist may cause eye irritation.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. A long-term NTP study showed that oral exposure to toluene diisocyanate (TDI) caused cancer in rats and mice. A lifetime inhalation study sponsored by the International Isocyanate Institute did not show carcinogenic activity in rats. May cause allergic skin and respiratory sensitization. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Eye, Lung, Liver, Kidney, Skin, Nerve

SECTION 3 - PRODUCT COMPOSITION

GEOGARD LO BASE COAT 2 GAL

Version 4.0

Print Date 05/30/2014

REVISION DATE: 07/08/2012

Chemical Name	CAS-No.	Weight %
Calcium Carbonate (Limestone)	1317-65-3	30.0 - 60.0
Polyurethane Polymer	NJ TSRN# 51721300-5024P	30.0 - 60.0
ASEP	70775-94-9	15.0 - 40.0
Tackifier	NJ TSRN# 51721300-5272P	7.0 - 13.0
Calcium oxide	1305-78-8	1.0 - 5.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1.0
2,4-Toluene diisocyanate	584-84-9	0.1 - 1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : > 100 °C, > 212 °F
- Method : Setflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Closed container, may burst when exposed to extreme heat. This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands



GEOGARD LO BASE COAT 2 GAL GEOGARD LO BASE COAT 2 GAL

Version 4.0

Print Date 05/30/2014

REVISION DATE: 07/08/2012

thoroughly after handling. Store under normal warehouse conditions in sealed containers.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Use full engineering controls before relying on personal protective equipment. Wear appropriate, properly fitted air purifying respirator with combination particulate filter and vapor/gas removing cartridge when airborne contaminant level(s) exceed exposure limits indicated on the MSDS, or product is spray applied.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Calcium oxide	1305-78-8	ACGIH TWA:	2 mg/m3	
		OSHA PEL:	5 mg/m3	
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Titanium dioxide	13463-67-7	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.
2,4-Toluene diisocyanate	584-84-9	ACGIH TWA:	0.005 ppm	
		ACGIH STEL:	0.02 ppm	

GEOGARD LO BASE COAT 2 GAL GEOGARD LO BASE COAT 2 GAL

Version 4.0

Print Date 05/30/2014

REVISION DATE: 07/08/2012

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: Gray
Odor	: Aliphatic Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Negligible
Specific Gravity	: 1.37
% Volatile Weight	: 0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Strong acids.Strong bases.Amines.Water or moisture.Alcohols.
Stability	: Material is stable under normal storage, handling, and use.
Hazardous polymerization	: Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

2,4-Toluene diisocyanate, CAS-No.: 584-84-9

Acute oral toxicity (LD-50 oral)	5,800 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	14 mg/l for 4 h (Rat) 10 mg/l for 4 h (Mouse) 13 mg/l for 4 h (Guinea pig) 11 mg/l for 4 h (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA**CFR / DOT:**

Not Regulated



GEOGARD LO BASE COAT 2 GAL GEOGARD LO BASE COAT 2 GAL

Version 4.0

Print Date 05/30/2014

REVISION DATE: 07/08/2012

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : 2,4-Toluene diisocyanate 584-84-9

SARA 311/312 Hazards : Acute Health Hazard
 Chronic Health Hazard

OSHA Hazardous Components :

Calcium Carbonate (Limestone) 1317-65-3
 Calcium oxide 1305-78-8
 Titanium dioxide 13463-67-7
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
 2,4-Toluene diisocyanate 584-84-9

OSHA Status: Considered : Irritant
 hazardous based on the Sensitizer
 following criteria: Carcinogen

OSHA Flammability : IIIB

Regulatory VOC (less water and : 11 g/l
 exempt solvent)

VOC Method 310 : 0 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components : Calcium Carbonate (Limestone) 1317-65-3
 Calcium oxide 1305-78-8
 Titanium dioxide 13463-67-7
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
 2,4-Toluene diisocyanate 584-84-9
 Toluene-2,6-Diisocyanate 91-08-7



GEOGARD LO BASE COAT 2 GAL GEOGARD LO BASE COAT 2 GAL

Version 4.0

Print Date 05/30/2014

REVISION DATE: 07/08/2012

Penn RTK Components	:	Calcium Carbonate (Limestone)	1317-65-3
		Polyurethane Polymer	NJ TSRN# 51721300-5024P
		ASEP	70775-94-9
		Tackifier	NJ TSRN# 51721300-5272P
		Calcium oxide	1305-78-8
		Titanium dioxide	13463-67-7
		2,4-Toluene diisocyanate	584-84-9
NJ RTK Components	:	Calcium Carbonate (Limestone)	1317-65-3
		Polyurethane Polymer	NJ TSRN# 51721300-5024P
		ASEP	70775-94-9
		Tackifier	NJ TSRN# 51721300-5272P
		Calcium oxide	1305-78-8
		Titanium dioxide	13463-67-7
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	1
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- | | |
|--|--|
| ACGIH - American Conference of Governmental Hygienists | PEL - Permissible Exposure Limit |
| CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act | RCRA - Resource Conservation and Recovery Act |
| DOT - Department of Transportation | RTK - Right To Know |
| DSL - Domestic Substance List | SARA - Superfund Amendments and Reauthorization Act |
| EPA - Environmental Protection Agency | STEL - Short Term Exposure Limit |
| HMIS - Hazardous Materials Information System | TLV - Threshold Limit Value |
| IARC - International Agency for Research on Cancer | TSCA - Toxic Substances Control Act |
| MSHA - Mine Safety Health Administration | TWA - Time Weighted Average |
| NDSL - Non-Domestic Substance List | V - Volume |
| NIOSH - National Institute for Occupational Safety and Health | VOC - Volatile Organic Compound |
| NTP - National Toxicology Program | WHMIS - Workplace Hazardous Materials Information System |
| OSHA - Occupational Safety and Health Administration | |