

Revision Date: 08/04/2015

# SAFETY DATA SHEET

# 1. Identification

Material name: GEOGARD LO BASE COAT 5 GL

Material: 491L005P

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

WATERPROOFING TECHNOLOGIES INC.

3735 Green road

**CLEVELAND OH 44124** 

US

Contact person:

**EH&S Department** 

Telephone:

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

#### **Hazard Classification**

#### **Health Hazards**

Respiratory sensitizer Category 1
Skin sensitizer Category 1

Carcinogenicity

Category 1A

# **Unknown toxicity - Health**

Acute toxicity, oral 51.86 %
Acute toxicity, dermal 54.31 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust or mist 99.62 %

# **Environmental Hazards**

Acute hazards to the aquatic Category 3

environment

# **Unknown toxicity - Environment**

Acute hazards to the aquatic 97.65 % environment
Chronic hazards to the aquatic 100 % environment

# **Label Elements**

# **Hazard Symbol:**





Revision Date: 08/04/2015

Signal Word:

Danger

**Hazard Statement:** 

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause cancer. Harmful to aquatic life.

Precautionary Statement: Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use personal protective equipment as required.

Response:

If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or

concerned: Get medical advice/attention. Specific treatment (see this label).

Wash contaminated clothing before reuse.

Storage:

Store locked up.

Disposal:

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*	
Calcium Carbonate (Limestone)	1317-65-3	30 - 60%	
Calcium oxide	1305-78-8	1 - 5%	
Titanium dioxide	13463-67-7	1 - 5%	
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	0.1 - 1%	
Hydrotreated heavy naphthenic distillate	64742-52-5	0.1 - 1%	
Dibutyl tin dilaurate	77-58-7	0.1 - 1%	
Tosyl isocyanate	4083-64-1	0.1 - 1%	
4,4'-Methylene bis(phenylisocyanate)	101-68-8	0.1 - 1%	
2,4-Toluene diisocyanate	584-84-9	0.1 - 1%	
Amorphous silica	7631-86-9	0.1 - 1%	
Polymethylene polyphenyl isocyanate	9016-87-9	0.1 - 1%	

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.



Revision Date: 08/04/2015

## 4. First-aid measures

Ingestion:

Rinse mouth thoroughly.

Inhalation:

Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give

oxygen.

**Skin Contact:** 

Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical

attention.

Eye contact:

Rinse immediately with plenty of water.

Most important symptoms/effects, acute and delayed

Symptoms:

May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment:

Symptoms may be delayed.

# 5. Fire-fighting measures

General Fire Hazards:

No unusual fire or explosion hazards noted.

# Suitable (and unsuitable) extinguishing media

Suitable extinguishing

Use fire-extinguishing media appropriate for surrounding materials.

media:

media:

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.



Revision Date: 08/04/2015

Methods and material for containment and cleaning

uр

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

**Notification Procedures:** 

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Environmental Precautions:** 

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

# 7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities:

Store locked up.

## 8. Exposure controls/personal protection

#### **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium Carbonate (Limestone) - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Calcium oxide	TWA	2 mg/m3	US. ACGIH Threshold Limit Values (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values (2011)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values (2011)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)





US. OSHA Table Z-3 (29 CFR 0.3 mg/m3 TWA Crystalline Silica 1910.1000) (2000) (Quartz)/ Silica Sand -Total dust. US. ACGIH Threshold Limit Values TWA 5 mg/m3 Hydrotreated heavy  $(03\ 2014)$ naphthenic distillate -Inhalable fraction. 2,000 US, OSHA Table Z-1 Limits for Air PEL 500 ppm Hydrotreated heavy Contaminants (29 CFR 1910.1000) mg/m3 naphthenic distillate  $(02\ 2006)$ US. OSHA Table Z-1 Limits for Air 5 mg/m3 PEL Hydrotreated heavy naphthenic distillate -Contaminants (29 CFR 1910.1000)  $(02\ 2006)$ Mist. US. ACGIH Threshold Limit Values 0.2 mg/m3 Dibutyl tin dilaurate - as STEL (2011)Sn US. ACGIH Threshold Limit Values  $0.1 \, \text{mg/m}3$ TWA (2011)US. OSHA Table Z-1 Limits for Air 0.1 mg/m3 PEL Contaminants (29 CFR 1910.1000)  $(02\ 2006)$ US. ACGIH Threshold Limit Values 4,4'-Methylene TWA 0.005 ppm (2011)bis(phenylisocyanate) US. OSHA Table Z-1 Limits for Air 0.02 ppm 0.2 mg/m3 Ceiling Contaminants (29 CFR 1910.1000)  $(02\ 2006)$ US. ACGIH Threshold Limit Values TWA 0.005 ppm 2,4-Toluene (2011)diisocyanate US. ACGIH Threshold Limit Values 0.02 ppm STEL (2011)US, OSHA Table Z-1 Limits for Air 0.02 ppm 0.14 Ceiling Contaminants (29 CFR 1910.1000) mg/m3  $(02\ 2006)$ 20 millions US. OSHA Table Z-3 (29 CFR TWA Amorphous silica of particles 1910.1000) (2000) per cubic foot of air 0.8 mg/m3 US. OSHA Table Z-3 (29 CFR **TWA** 1910.1000) (2000) US. ACGIH Threshold Limit Values Polymethylene TWA 0.005 ppm (2011)polyphenyl isocyanate US. OSHA Table Z-1 Limits for Air 0.02 ppm 0.2 mg/m3 Ceiling Contaminants (29 CFR 1910.1000)  $(02\ 2006)$ 

Chemical name	type	Exposure Limit Values	Source
Calcium Carbonate (Limestone) - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)





Revision Date: 08/04/2015

Calcium Carbonate (Limestone) - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium Carbonate (Limestone) - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Calcium oxide	TWA	2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium oxide	TWAEV	2 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Calcium oxide	TWA	2 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWAEV	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWAEV	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Hydrotreated heavy naphthenic distillate - Mist.	TWA	0.2 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97 as amended) (05 2013)
	TWA	1 mg/m3	Canada. British Columbia OELs.

TREMCO.





Revision Date: 08/04/2015

			×	(Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (05 2013)
Hydrotreated heavy naphthenic distillate - Mist.	TWAEV		5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	STEL		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Hydrotreated heavy naphthenic distillate - Mist.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
4,4'-Methylene bis(phenylisocyanate)	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ale es	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
4,4'-Methylene	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of
bis(phenylisocyanate)				Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
4,4'-Methylene bis(phenylisocyanate)	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
2,4-Toluene diisocyanate	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
2,4-Toluene diisocyanate	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)



Revision Date: 08/04/2015

2,4-Toluene diisocyanate	TWA	0.005 ppm	0.036 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
	STEL	0.02 ppm	0.14 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	0.005 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	CEILING	0.01 ppm	ē	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Polymethylene polyphenyl isocyanate	TWAEV	0.005 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
	CEV	0.02 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Polymethylene polyphenyl isocyanate	TWA	0.005 ppm	0.051 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

# Individual protection measures, such as personal protective equipment

General information:

Use personal protective equipment as required.

Eye/face protection:

Wear goggles/face shield.

**Skin Protection** 

**Hand Protection:** 

Use suitable protective gloves if risk of skin contact.

Other:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.



Revision Date: 08/04/2015

If engineering controls do not maintain airborne concentrations below **Respiratory Protection:** 

recommended exposure limits (where applicable) or to an acceptable level

(in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter,

cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

Observe good industrial hygiene practices. Wash hands before breaks and Hygiene measures:

immediately after handling the product. Contaminated work clothing should

not be allowed out of the workplace. Avoid contact with skin.

# 9. Physical and chemical properties

**Appearance** 

Physical state: liquid

liquid Form:

Color: Gray

Mild petroleum/solvent Odor:

No data available. Odor threshold: No data available. pH:

Melting point/freezing point: No data available.

No data available. Initial boiling point and boiling range:

> 100 °C > 212 °F(Setaflash Closed Cup) Flash Point:

Slower than Ether **Evaporation rate:** 

No Flammability (solid, gas):

Upper/lower limit on flammability or explosive limits

Flammability limit - lower (%):

No data available. Flammability limit - upper (%): No data available.

No data available. Explosive limit - upper (%):

No data available. Explosive limit - lower (%): No data available.

Vapor pressure: Vapors are heavier than air and may travel along the floor and Vapor density:

in the bottom of containers.

1.37 Relative density:

Solubility(ies) Practically Insoluble Solubility in water:

Solubility (other): No data available. No data available.

Partition coefficient (n-octanol/water): No data available. Auto-ignition temperature:

No data available. Decomposition temperature:

No data available. Viscosity:

# 10. Stability and reactivity

Reactivity: No data available.



Revision Date: 08/04/2015

**Chemical Stability:** 

Material is stable under normal conditions.

Possibility of Hazardous

Reactions:

No data available.

Conditions to Avoid:

Avoid heat or contamination.

Incompatible Materials:

Alcohols. Amines. Strong acids. Strong bases. Water, moisture.

**Hazardous Decomposition** 

**Products:** 

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

# 11. Toxicological information

Information on likely routes of exposure

Ingestion:

May be ingested by accident. Ingestion may cause irritation and malaise.

Inhalation:

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

**Skin Contact:** 

May cause an allergic skin reaction.

Eye contact:

Eye contact is possible and should be avoided.

# Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:

ATEmix: 64,966.26 mg/kg

Dermal

Product:

ATEmix: 61,654.52 mg/kg

Inhalation

**Product:** 

No data available.

Repeated dose toxicity

**Product:** 

No data available.

Skin Corrosion/Irritation

**Product:** 

No data available.

Serious Eye Damage/Eye Irritation

**Product:** 

No data available.



Revision Date: 08/04/2015

Specified substance(s):

Calcium oxide

in vivo (Rabbit, 24 hrs): Category 1

Titanium dioxide

in vivo (Rabbit, 24 - 72 hrs): Not irritating

Hydrotreated heavy naphthenic distillate

in vivo (Rabbit, 24 hrs): Not irritating

Dibutyl tin dilaurate

in vivo (Rabbit, 24 hrs): Highly irritating

4,4'-Methylene bis(phenylisocyanate)

in vivo (Rabbit, 24 - 72 hrs): Not irritating

2,4-Toluene

in vivo (Rabbit, 24 - 72 hrs): Category 2

diisocyanate

Amorphous silica

in vivo (Rabbit, 24 hrs): Not irritating

Respiratory or Skin Sensitization

Product:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

Product:

No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide

Overall evaluation: Possibly carcinogenic to humans.

Crystalline Silica

Overall evaluation: Carcinogenic to humans.

(Quartz)/ Silica

Sand

Hydrotreated heavy

Overall evaluation: Not classifiable as to carcinogenicity to humans. Overall

naphthenic distillate evaluation: Carcinogenic to humans.

2,4-Toluene

diisocyanate

Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline

Silica Known To Be Human Carcinogen. Silica

(Quartz)/

Sand

Hydrotreated heavy

Known To Be Human Carcinogen.

naphthenic distillate

2,4-Toluene

Reasonably Anticipated to be a Human Carcinogen.

diisocyanate

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified



Revision Date: 08/04/2015

**Germ Cell Mutagenicity** 

In vitro

Product:

No data available.

In vivo

**Product:** 

No data available.

Reproductive toxicity

Product:

No data available.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** 

No data available.

**Specific Target Organ Toxicity - Repeated Exposure** 

Product:

No data available.

**Aspiration Hazard** 

**Product:** 

No data available.

Other effects:

No data available.

# 12. Ecological information

### **Ecotoxicity:**

## Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Titanium dioxide

LC 50 (Mummichog (Fundulus heteroclitus), 96 h): > 1,000 mg/l Mortality

Dibutyl tin dilaurate

LC 50 (Ide, silver or golden orfe (Leuciscus idus), 48 h): 2 mg/l Mortality

2,4-Toluene diisocyanate

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 108.8 - 240.4 mg/l

Mortality

**Aquatic Invertebrates** 

Product:

No data available.

Specified substance(s):

Titanium dioxide

EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

Dibutyl tin dilaurate

EC 50 (Water flea (Daphnia magna), 24 h): 0.66 mg/l Intoxication

Chronic hazards to the aquatic environment:

Fish

**Product:** 

No data available.



Revision Date: 08/04/2015

Specified substance(s):

Calcium oxide

NOAEL (Oncorhynchus mykiss, 60 d): 307 mg/l interpreted

Titanium dioxide

LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental

result

Hydrotreated heavy naphthenic distillate

NOAEL (Oncorhynchus mykiss, 14 d): >= 1,000 mg/l QSAR

**Aquatic Invertebrates** 

Product:

No data available.

**Toxicity to Aquatic Plants** 

Product:

No data available.

Persistence and Degradability

Biodegradation

Product:

No data available.

**BOD/COD Ratio** 

**Product:** 

No data available.

**Bioaccumulative Potential** 

**Bioconcentration Factor (BCF)** 

Product:

No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:

No data available.

Specified substance(s):

Dibutyl tin dilaurate

Log Kow: 3.12

Mobility in Soil:

No data available.

Other Adverse Effects:

Harmful to aquatic organisms.

13. Disposal considerations

Disposal instructions:

Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

**Contaminated Packaging:** 

No data available.

14. Transport information

TDG:

Not Regulated

13/17



Revision Date: 08/04/2015

### CFR / DOT:

Not Regulated

#### IMDG:

Not Regulated

# 15. Regulatory information

## **US Federal Regulations**

# TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

**Chemical Identity** 

Reportable quantity

2,4-Toluene diisocyanate

De minimis concentration: 0.1% One-Time Export Notification only.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

#### **CERCLA Hazardous Substance List (40 CFR 302.4):**

**Chemical Identity** Reportable quantity 4,4'-Methylene 5000 lbs. bis(phenylisocyanate) 2,4-Toluene diisocyanate 100 lbs. Polymethylene 5000 lbs. polyphenyl isocyanate 100 lbs.

Toluene-2,6-Diisocyanate Methanol 5000 lbs. Chlorobenzene 100 lbs.

Ethylbenzene

1000 lbs.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Delayed (Chronic) Health Hazard Immediate (Acute) Health Hazards

#### SARA 302 Extremely Hazardous Substance

Reportable

**Chemical Identity** quantity 2,4-Toluene diisocyanate

Toluene-2,6-Diisocyanate

100 lbs. 100 lbs.

**Threshold Planning Quantity** 

500 lbs. 100 lbs.



Revision Date: 08/04/2015

# SARA 304 Emergency Release Notification

Chemical Identity 4,4'-Methylene Reportable quantity 5000 lbs.

bis(phenylisocyanate)

2,4-Toluene diisocyanate 100 lbs.

Diisodecyl phthalate

Polymethylene 5000 lbs.

polyphenyl isocyanate

Toluene-2,6-Diisocyanate Methanol

te 100 lbs. 5000 lbs.

Diisodecyl phthalate

(mixed Is)

Chlorobenzene Ethylbenzene

100 lbs. 1000 lbs.

SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
2,4-Toluene diisocyanate	500lbs
Toluene-2,6-Diisocyanate	100lbs
Calcium Carbonate	500 lbs
(Limestone)	
Calcium oxide	500 lbs
Titanium dioxide	500 lbs
Crystalline Silica (Quartz)/	500 lbs
Silica Sand	
Hydrotreated heavy	500 lbs
naphthenic distillate	
Dibutyl tin dilaurate	500 lbs
Tosyl isocyanate	500 lbs

Tosyl isocyanate 4,4'-Methylene

500 lbs 500 lbs

bis(phenylisocyanate)

Amorphous silica

500 lbs

Polymethylene polyphenyl

500 lbs

isocyanate

# SARA 313 (TRI Reporting)

#### **Chemical Identity**

2,4-Toluene diisocyanate

# Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Chemical Identity Reportable quantity

2,4-Toluene diisocyanate 10000 lbs Toluene-2,6-Diisocyanate 10000 lbs

US State Regulations

# **US. California Proposition 65**

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.



Revision Date: 08/04/2015

## US. New Jersey Worker and Community Right-to-Know Act

#### **Chemical Identity**

Calcium Carbonate (Limestone)

Calcium oxide

Titanium dioxide

#### **US. Massachusetts RTK - Substance List**

### **Chemical Identity**

Calcium Carbonate (Limestone)

Calcium oxide

Titanium dioxide

Crystalline Silica (Quartz)/ Silica Sand

2,4-Toluene diisocyanate

Toluene-2,6-Diisocyanate

# US. Pennsylvania RTK - Hazardous Substances

### **Chemical Identity**

Calcium Carbonate (Limestone)

Calcium oxide

Titanium dioxide

2,4-Toluene diisocyanate

#### US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

# Other Regulations:

Regulatory VOC (less water

11 g/l

and exempt solvent):

VOC Method 310: 0.71 %

#### **Inventory Status:**

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List:

One or more components in this product are not listed on or exempt from the Inventory.

EINECS, ELINCS or NLP:

One or more components in this product are not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI):

One or more components in this product are not listed on or exempt from the Inventory.

Canada NDSL Inventory:

One or more components in this product are not listed on or exempt from the Inventory.



Revision Date: 08/04/2015

Philippines PICCS:

One or more components in this product are not listed on or exempt from the Inventory.

US TSCA Inventory:

One or more components in this product are not listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are not listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are not listed on or exempt from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

**Revision Date:** 

08/04/2015

Version #:

1.0

**Further Information:** 

No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.