

GEOGARD PRIMER 1 GALGEOGARD PRIMER 1 GAL

Version 3.0

REVISION DATE: 07/08/2012

Print Date 08/14/2015

SECTION 1 - PRODUCT IDENTIFICATION

Trade name

Product code

49401C

COMPANY

Tremco Incorporated 3735 Green Road Cleveland, OH 44122

Telephone

(216) 292-5000 8:30 - 5:00 EST (216) 765-6727 8:30 - 5:00 EST

Emergency Phone:

After Hours: Chemtrec 1-800-424-9300

Product use

Coating

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Clear to Yellow. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation

May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic

respiratory sensitization.

Eyes

Vapor and/or mist may cause eye irritation.

Ingestion

May cause irritation to the mouth, throat and stomach. May cause gastrointestinal

irritation, nausea, and vomiting.

Skin

May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Prolonged inhalation or ingestion of large amounts of 1-chloro-4-(trifluoromethyl)-benzene may cause liver and kidney damage based on laboratory animal studies. Diphenylmethane diisocyanate (methylene bisphenyl isocyanate) caused an increased incidence of lung tumors in experimental animals following long term inhalation at concentrations in excess of 100 times the exposure limit. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Eye, Lung, Liver, Kidney, Skin, Nerve

SECTION 3 - PRODUCT COMPOSITION

Chemical Name

CAS-No.

Weight %

An RPM Company 1/6

6 49401C

Material Safety Data Sheet



GEOGARD PRIMER 1 GALGEOGARD PRIMER 1 GAL

Version 3.0

REVISION DATE: 07/08/2012

Print Date 08/14/2015

P-chlorobenzotrifluoride

98-56-6

> 60.0

Urethane polymer

NJ TSRN# 51721300-6109P

30.0 - 60.0

4,4'-Methylene bis(phenylisocyanate)

101-68-8

1.0 - 5.0

Diphenylmethane diisocyanate

26447-40-5

1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

Inhalation

: Move to fresh air. If required, artificial respiration or administration of oxygen can be

performed by trained personnel. Leave area to breathe fresh air. Avoid further

overexposure. If symptoms persist, get medical attention.

Eye contact

Flush with water for at least 15 minutes while holding eye lids apart. Get medical

attention immediately.

Skin contact

: Wash area of contact thoroughly with hand cleaner followed by soap and water. If

irritation, rash or other disorders develop, get medical attention immediately.

Ingestion

Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

Flash point

109 °F, 43 °C

Method

Not available.

Lower explosion limit

Not available.

Upper explosion limit

Not available.

Autoignition temperature

Not available.

Extinguishing media

If water fog is ineffective, use carbon dioxide, dry chemical or foam.

Hazardous combustion

products

Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.

Protective equipment for

firefighters

Use accepted fire fighting techniques. Wear full firefighting protective

clothing, including self-contained breathing apparatus (SCBA).

Fire and explosion conditions

Product may ignite if heated in excess of its flash point.Closed

container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition

and flashback.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store

An RPM Company 2/6



GEOGARD PRIMER 1 GALGEOGARD PRIMER 1 GAL

Version 3.0

REVISION DATE: 07/08/2012

Print Date 08/14/2015

under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

Respiratory protection

Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator

(TC19C or equivalent) for isocyanates.

Hand protection

Use suitable impervious nitrile or neoprene gloves and protective apparel to

reduce exposure.

Eye protection

Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily

available.

Skin and body protection

Prevent contact with shoes and clothing.

Protective measures

Use professional judgment in the selection, care, and use.

Engineering measures

: Use only in well ventilated areas. Provide maximum ventilation in enclosed

areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
4,4'-Methylene	101-68-8	ACGIH TWA:	0.005 ppm	
bis(phenylisocyanate)				

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form

: Liquid

Color

: Clear to Yellow

Odor

Solvent

рΗ

: Not available.

Vapour pressure

: Not available.

Vapor density

: Heavier than air

Melting point/range

Not available.

Freezing point

: Not available.

Boiling point/range

: Not available.

Water solubility
Specific Gravity

: Negligible

Opcomo Gravity

: 1.21

% Volatile Weight

: 63 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid

3/6

Strong acids. Strong bases. Amines. Water or moisture. Alcohols.

An RPITT Company

Material Safety Data Sheet



GEOGARD PRIMER 1 GALGEOGARD PRIMER 1 GAL

Version 3.0 Print Date 08/14/2015

REVISION DATE: 07/08/2012

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

4,4'-Methylene bis(phenylisocyanate), CAS-No.: 101-68-8

Acute inhalation toxicity (LC-50) 0.369 mg/l for 4 h (Rat) 0.38 mg/l for 4 h (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)

This classification applies only to the material as it was originally produced.

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under

RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in

compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory. One or more components are listed on the NDSL.

U.S. Federal Regulations:

An **RPIII** Company 4/6 49401C



GEOGARD PRIMER 1 GALGEOGARD PRIMER 1 GAL

Version 3.0

REVISION DATE: 07/08/2012

Print Date 08/14/2015

SARA 313 Components

4,4'-Methylene bis(phenylisocyanate)

101-68-8

SARA 311/312 Hazards

Acute Health Hazard

Fire Hazard

OSHA Hazardous Components:

4,4'-Methylene bis(phenylisocyanate)

101-68-8

OSHA Status: Considered

hazardous based on the

: Irritant Sensitizer

following criteria:

OSHA Flammability : II

Regulatory VOC (less water and 79 g/l

exempt solvent)

VOC Method 310

: 3%

U.S. State Regulations:

MASS RTK Components 4,4'-Methylene bis(phenylisocyanate)

101-68-8

Penn RTK Components P-chlorobenzotrifluoride

98-56-6

Urethane polymer

NJ TSRN# 51721300-6109P

4,4'-Methylene bis(phenylisocyanate)

101-68-8

NJ RTK Components

: P-chlorobenzotrifluoride

Urethane polymer

98-56-6 NJ TSRN# 51721300-6109P

4,4'-Methylene bis(phenylisocyanate) Diphenylmethane diisocyanate

101-68-8

26447-40-5

Components under California Proposition 65:

None known.

SECTION 16 - OTHER INFORMATION

HMIS Rating:

Health	2	
Flammability	2	
Reactivity	2	
PPE		

0 = Minimum

1 = Slight2 = Moderate

3 = Serious 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists CERCLA - Comprehensive Environmental Response, Compensation, and

PEL - Permissible Exposure Limit

the series with the state of the series

RCRA - Resource Conservation and Recovery Act



Material Safety Data Sheet



GEOGARD PRIMER 1 GALGEOGARD PRIMER 1 GAL

Version 3.0

REVISION DATE: 07/08/2012

Print Date 08/14/2015

Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System