



GEOGARD PRIMER 1 GAL

Version 1.0
REVISION DATE: 05/14/2014

Print Date 08/15/2015

SECTION 1 - PRODUCT IDENTIFICATION

Trade name	:	GEOGARD PRIMER 1 GAL
Product code	:	494QD01C
COMPANY	:	Tremco Incorporated 3735 Green Road Cleveland, OH 44122
Telephone	:	(216) 292-5000 8:30 - 5:00 EST
Emergency Phone	:	(216) 765-6727 8:30 - 5:00 EST After Hours: Chemtrec 1-800-424-9300
Product use	:	Coating

RECEIVED
15 JUN 25 10 59 AM '15

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Clear to Amber. Liquid. May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation	:	May cause drowsiness, weakness, and fatigue. Vapor and/or mist may irritate nose and throat. May cause moderate irritation to the respiratory system. May cause allergic respiratory sensitization.
Eyes	:	Vapor and/or mist may cause eye irritation.
Ingestion	:	May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.
Skin	:	May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Overexposure may cause dermatitis, asthma, skin and respiratory sensitization and decreased lung function. Repeated overexposure to vapors and/or material may injure the liver, kidneys and respiratory system unless suitable engineering controls and/or personal protective equipment are used. Prolonged inhalation or ingestion of large amounts of 1-chloro-4-(trifluoromethyl)-benzene may cause liver and kidney damage based on laboratory animal studies. Diphenylmethane diisocyanate (methylene bisphenyl isocyanate) caused an increased incidence of lung tumors in experimental animals following long term inhalation at concentrations in excess of 100 times the exposure limit. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Eye, Lung, Liver, Kidney, Skin, Nerve

GEOGARD PRIMER 1 GALVersion 1.0
REVISION DATE: 05/14/2014

Print Date 08/15/2015

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
P-chlorobenzotrifluoride	98-56-6	40.0 - 70.0
Polyurethane Resin	NJ TSN# 51721300-6392P	30.0 - 60.0
4,4'-Methylene bis(phenylisocyanate)	101-68-8	1.0 - 5.0
Diphenylmethane diisocyanate	26447-40-5	1.0 - 5.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : 43 °C, 109 °F
- Method : Setaflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Smoke, fumes. Hydrocyanic acid and nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Product may ignite if heated in excess of its flash point. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors. Vapors may travel to sources of ignition and flashback.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.



GEOGARD PRIMER 1 GAL

Version 1.0
 REVISION DATE: 05/14/2014

Print Date 08/15/2015

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Change soiled work clothes frequently. Clean hands thoroughly after handling. Do not smoke, weld, generate sparks, or use flame near container. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Select positive pressure supplied air respirator (TC19C or equivalent) for isocyanates.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Skin and body protection : Prevent contact with shoes and clothing.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
4,4'-Methylene bis(phenylisocyanate)	101-68-8	ACGIH TWA:	0.005 ppm	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid
- Color : Clear to Amber
- Odor : Solvent
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.



GEOGARD PRIMER 1 GAL

Version 1.0
REVISION DATE: 05/14/2014

Print Date 08/15/2015

Water solubility : Negligible
Specific Gravity : 1.21
% Volatile Weight : 60 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Strong acids.Strong bases.Amines.Water or moisture.Alcohols.
Stability : Material is stable under normal storage, handling, and use.
Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

4,4'-Methylene bis(phenylisocyanate), CAS-No.: 101-68-8
Acute inhalation toxicity (LC-50) 0.369 mg/l for 4 h (Rat) 0.38 mg/l for 4 h (Rat)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)
This classification applies only to the material as it was originally produced.
Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

UN1139, COATING SOLUTION, 3, PG III

Further Information:



GEOGARD PRIMER 1 GAL

Version 1.0
 REVISION DATE: 05/14/2014

Print Date 08/15/2015

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory. One or more components are listed on the NDSL.

U.S. Federal Regulations:

SARA 313 Components : 4,4'-Methylene bis(phenylisocyanate) 101-68-8

SARA 311/312 Hazards : Acute Health Hazard
 Fire Hazard

OSHA Hazardous Components :

4,4'-Methylene bis(phenylisocyanate) 101-68-8

OSHA Status: Considered : Irritant
 hazardous based on the Sensitizer
 following criteria:

OSHA Flammability : II

Regulatory VOC (less water and : 5 g/l
 exempt solvent)

VOC Method 310 : 0.18 %

U.S. State Regulations:

MASS RTK Components : 4,4'-Methylene bis(phenylisocyanate) 101-68-8

Penn RTK Components : P-chlorobenzotrifluoride 98-56-6
 Polyurethane Resin NJ TSRN# 51721300-6392P
 4,4'-Methylene bis(phenylisocyanate) 101-68-8

NJ RTK Components : P-chlorobenzotrifluoride 98-56-6
 Polyurethane Resin NJ TSRN# 51721300-6392P
 4,4'-Methylene bis(phenylisocyanate) 101-68-8
 Diphenylmethane diisocyanate 26447-40-5

Components under California Proposition 65:
 None known.



GEOGARD PRIMER 1 GAL

Version 1.0
 REVISION DATE: 05/14/2014

Print Date 08/15/2015

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	2
Reactivity	0
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
 CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
 DOT - Department of Transportation
 DSL - Domestic Substance List
 EPA - Environmental Protection Agency
 HMIS - Hazardous Materials Information System
 IARC - International Agency for Research on Cancer
 MSHA - Mine Safety Health Administration
 NDSL - Non-Domestic Substance List
 NIOSH - National Institute for Occupational Safety and Health
 NTP - National Toxicology Program
 OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
 RCRA - Resource Conservation and Recovery Act
 RTK - Right To Know
 SARA - Superfund Amendments and Reauthorization Act
 STEL - Short Term Exposure Limit
 TLV - Threshold Limit Value
 TSCA - Toxic Substances Control Act
 TWA - Time Weighted Average
 V - Volume
 VOC - Volatile Organic Compound
 WHMIS - Workplace Hazardous Materials Information System