



UNCURED FLASHING 6" RL (2 ROLLS = CASE)

Version 3.0
 REVISION DATE: 12/18/2013

Print Date 05/15/2014

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : **UNCURED FLASHING 6" RL (2 ROLLS = CASE)**
 Product code : 68206B503
 COMPANY : Tremco Incorporated
 3735 Green Road
 Cleveland, OH 44122
 Telephone : (216) 292-5000 8:30 - 5:00 EST
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
 After Hours: Chemtrec 1-800-424-9300
 Product use : Tape

RECEIVED KODA
 14 MAY 20 PM 1:28

SECTION 2 - HAZARDS IDENTIFICATION

Emergency Overview

Solid. No serious effects anticipated under normal conditions of use. Generally not required under normal conditions of use.

Acute Potential Health Effects/ Routes of Entry

Inhalation : No serious effects anticipated under normal conditions of use.
 Eyes : Not applicable under normal conditions of use. Direct contact may cause temporary redness and discomfort.
 Ingestion : No known adverse effects.
 Skin : No effects anticipated.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. Overexposure to sublimed zinc oxide may produce symptoms known as "zinc oxide chills" which have no recognized complications. Symptoms usually disappear within 24 hours. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
EPDM Membrane	NJ TSRN# 51721300-5314P	40.0 - 70.0
Olefin Polymer	NJ TSRN# 51721300-5309P	15.0 - 40.0
Synthetic Rubber	NJ TSRN# 51721300-5310P	15.0 - 40.0
Carbon Black	1333-86-4	1.0 - 5.0
Phenolic Resin	NJ TSRN# 51721300-5311P	1.0 - 5.0
Zinc oxide	1314-13-2	1.0 - 5.0

UNCURED FLASHING 6" RL (2 ROLLS = CASE)Version 3.0
REVISION DATE: 12/18/2013

Print Date 05/15/2014

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Generally not required under normal conditions of use.
- Eye contact : Generally not required under normal conditions of use.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Get medical attention. Do not induce vomiting.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : 230 °F, 110 °C
- Method : Setflash Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Handle in compliance with common hygienic practices. Clean hands thoroughly after handling. Store under dry warehouse conditions away from heat and all ignition sources.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Generally not required under normal conditions of use. Use safety glasses if eye contact is likely.
- Skin and body protection : Not required.
- Protective measures : Other equipment not normally required. Use professional judgment in the selection, care, and use.



UNCURED FLASHING 6" RL (2 ROLLS = CASE)

Version 3.0
 REVISION DATE: 12/18/2013

Print Date 05/15/2014

Engineering measures : Not required under normal conditions of use. Use only in well ventilated areas. Provide maximum ventilation in enclosed areas.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Carbon Black	1333-86-4	ACGIH TWA:	3.5 mg/m ³	Total dust. Respirable fraction.
		OSHA PEL:	3.5 mg/m ³	
		OSHA TWA:	15 mg/m ³	
		OSHA TWA:	5 mg/m ³	
Zinc oxide	1314-13-2	ACGIH TWA:	2 mg/m ³	Respirable fraction.
		ACGIH STEL:	10 mg/m ³	Respirable fraction.
		OSHA PEL:	5 mg/m ³	Fume.
		OSHA PEL:	5 mg/m ³	Respirable fraction.
		OSHA PEL:	15 mg/m ³	Total dust.
		OSHA TWA:	15 mg/m ³	Total dust.
		OSHA TWA:	5 mg/m ³	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form : Solid
 Odor : Negligible
 pH : Not available.
 Vapour pressure : Not available.
 Vapor density : Heavier than air
 Melting point/range : Not available.
 Freezing point : Not available.
 Boiling point/range : Not available.
 Water solubility : Insoluble
 Specific Gravity : 0.890 at 77 °F
 % Volatile Weight : 0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Oxidizing agents.
 Stability : Material is stable under normal storage, handling, and use.
 Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Zinc oxide, CAS-No.: 1314-13-2
 Acute oral toxicity (LD-50 oral) 7,950 mg/kg (Mouse) 7,950 mg/kg (Mouse)



UNCURED FLASHING 6" RL (2 ROLLS = CASE)

Version 3.0
 REVISION DATE: 12/18/2013

Print Date 05/15/2014

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.
 This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : Zinc oxide 1314-13-2

SARA 311/312 Hazards : Chronic Health Hazard

OSHA Hazardous Components :

Carbon Black 1333-86-4
 Zinc oxide 1314-13-2

OSHA Status: Considered : Carcinogen
 hazardous based on the
 following criteria:

OSHA Flammability : III B

Regulatory VOC (less water and
 exempt solvent) : 0 g/l



UNCURED FLASHING 6" RL (2 ROLLS = CASE)

Version 3.0
 REVISION DATE: 12/18/2013

Print Date 05/15/2014

VOC Method 310 : 0.00 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:
 Carbon Black 1333-86-4

U.S. State Regulations:

- MASS RTK Components : Carbon Black 1333-86-4
 Zinc oxide 1314-13-2
- Penn RTK Components : EPDM Membrane NJ TSRN# 51721300-5314P
 Olefin Polymer NJ TSRN# 51721300-5309P
 Synthetic Rubber NJ TSRN# 51721300-5310P
 Carbon Black 1333-86-4
 Zinc oxide 1314-13-2
- NJ RTK Components : EPDM Membrane NJ TSRN# 51721300-5314P
 Olefin Polymer NJ TSRN# 51721300-5309P
 Synthetic Rubber NJ TSRN# 51721300-5310P
 Carbon Black 1333-86-4
 Phenolic Resin NJ TSRN# 51721300-5311P
 Zinc oxide 1314-13-2

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	1
Flammability	1
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List

- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume



UNCURED FLASHING 6" RL (2 ROLLS = CASE)

Version 3.0
REVISION DATE: 12/18/2013

Print Date 05/15/2014

NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System