

Revision Date: 10/07/2015

SAFETY DATA SHEET

1. Identification

Material name: TREMSEAL D LIMESTONE LV 30 TUBES/CS

Material: 876153 309

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

WATERPROOFING TECHNOLOGIES INC.

3735 Green road Beachwood OH 44122 US

Contact person:

EH&S Department

Telephone:

Emergency telephone number:

1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Respiratory sensitizer Category 1
Skin sensitizer Category 1
Germ Cell Mutagenicity Category 1B
Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 13.95 %
Acute toxicity, dermal 18.17 %
Acute toxicity, inhalation, vapor 94.7 %
Acute toxicity, inhalation, dust or mist 99.96 %

Environmental Hazards

Acute hazards to the aquatic Category 1 environment

Unknown toxicity - Environment

Acute hazards to the aquatic 74.22 % environment
Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Revision Date: 10/07/2015



Signal Word:

Danger

Hazard Statement:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

May cause genetic defects.

May cause cancer.
Very toxic to aquatic life.

Precautionary
Statement:
Prevention:

Avoid breathing dust/fume/gas/mist/vapors/spray. [In case of inadequate ventilation] wear respiratory protection. Contaminated work clothing must

not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and

understood. Use personal protective equipment as required. Avoid release

to the environment.

Response: If inhaled: If breathing is difficult, remove person to fresh air and keep

comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER/doctor. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. If exposed or

concerned: Get medical advice/attention. Specific treatment (see this label).

Wash contaminated clothing before reuse. Collect spillage.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Other hazards which do not result in GHS classification:

None.

3. Composition/information on ingredients

Mixtures

| Chemical Identity | CAS number | Content in percent (%)* |
|---|------------|-------------------------|
| Calcium Carbonate (Limestone) | 1317-65-3 | 10 - 30% |
| Heavy aromatic naphtha | 64742-94-5 | 3 - 7% |
| Titanium dioxide | 13463-67-7 | 3 - 7% |
| Aromatic petroleum distillates | 64742-95-6 | 0.5 - 1.5% |
| 4,4'-Methylene bis(phenylisocyanate) | 101-68-8 | 0.5 - 1.5% |
| 1,2,4-Trimethylbenzene | 95-63-6 | 0.5 - 1.5% |
| Polymethylene polyphenyl isocyanate | 9016-87-9 | 0.1 - 1% |



Revision Date: 10/07/2015

| Aluminum oxide | 1344-28-1 | 0.1 - 1% |
|---|------------|----------|
| 1,3,5-Trimethylbenzene | 108-67-8 | 0.1 - 1% |
| Crystalline Silica (Quartz)/ Silica Sand | 14808-60-7 | 0.1 - 1% |

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:

Call a POISON CENTER/doctor/.../if you feel unwell. Rinse mouth.

Inhalation:

Call a physician or poison control center immediately. If breathing stops, provide artificial respiration. Move to fresh air. If breathing is difficult, give

oxygen.

Skin Contact:

Eye contact:

If skin irritation occurs: Get medical advice/attention. Destroy or thoroughly clean contaminated shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get medical attention.

Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get

medical advice/attention.

Most important symptoms/effects, acute and delayed

Symptoms:

May cause skin and eye irritation.

Indication of immediate medical attention and special treatment needed

Treatment:

Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards:

No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

Do not use water jet as an extinguisher, as this will spread the fire.

media:

Specific hazards arising from the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Special fire fighting

No data available.

procedures:

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

hters: worn in case of fire.



Revision Date: 10/07/2015

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. Evacuate area. See Section 8 of the SDS for Personal Protective Equipment. Keep upwind. Keep unauthorized personnel away. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Methods and material for containment and cleaning up:

Collect spillage in containers, seal securely and deliver for disposal according to local regulations.

Notification Procedures:

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

Environmental Precautions:

Avoid release to the environment. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling:

Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Wash hands thoroughly after handling. Ventilate well, avoid breathing vapors. Use approved respirator If air contamination is above accepted level. Use mechanical ventilation in case of handling which causes formation of dust.

Conditions for safe storage, including any incompatibilities:

Store locked up.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

| Chemical Identity | type | Exposure Limit V | /alues | Source |
|---|------|------------------|--------------|---|
| Calcium Carbonate (Limestone) - Total dust. | PEL | 15 | mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Calcium Carbonate (Limestone) - Respirable fraction. | PEL | 5 | mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor | TWA | | 200 mg/m3 | US. ACGIH Threshold Limit Values (03 2014) |
| Heavy aromatic naphtha | PEL | 100 ppm | 400 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Titanium dioxide | TWA | 10 | mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Titanium dioxide - Total dust. | PEL | 15 | mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |





Revision Date: 10/07/2015

| 4,4'-Methylene bis(phenylisocyanate) | TWA | 0.005 ppm | US. ACGIH Threshold Limit Values (2011) |
|---|---------|---|---|
| | Ceiling | 0.02 ppm 0.2 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | US. ACGIH Threshold Limit Values (2011) |
| Polymethylene polyphenyl isocyanate | TWA | 0.005 ppm | US. ACGIH Threshold Limit Values (2011) |
| , | Ceiling | 0.02 ppm 0.2 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Respirable fraction. | TWA | 1 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| u. V égek ap sa nom taki nc | PEL | 5 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| Aluminum oxide - Total dust. | PEL | 15 mg/m3 | US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | US. ACGIH Threshold Limit Values (2011) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | 0.025 mg/m3 | US. ACGIH Threshold Limit Values (2011) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable. | TWA | 2.4 millions of particles per cubic foot of air | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| | TWA | 0.1 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |
| Crystalline Silica (Quartz)/ Silica Sand - Total dust. | TWA | 0.3 mg/m3 | US. OSHA Table Z-3 (29 CFR 1910.1000) (2000) |

| Chemical name | type | Exposure Limit Values | Source |
|---|-------|-----------------------|---|
| Diisodecyl phthalate | TWAEV | 5 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Calcium Carbonate (Limestone) - Total dust. | STEL | 20 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 10 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |



Revision Date: 10/07/2015

| Calcium Carbonate (Limestone) - Respirable fraction. | TWA | 3 mg/m | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
|---|---------|----------------------|---|
| Calcium Carbonate (Limestone) - Total dust. | TWA | 10 mg/m | |
| Heavy aromatic naphtha - Non-aerosol, - as total hydrocarbon vapor | TWA | 20 mg/m | |
| Heavy aromatic naphtha - Non-aerosol. - as total hydrocarbon vapor | TWAEV | 2(mg/n | OO Canada. Ontario OELs. (Control of |
| Heavy aromatic naphtha | TWA | 400 ppm 1,59 mg/m | , , , |
| Titanium dioxide - Total dust. | TWA | 10 mg/n | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide - Respirable fraction. | TWA | 3 mg/n | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Titanium dioxide | TWAEV | 10 mg/m | |
| Titanium dioxide - Total dust. | TWA | 10 mg/n | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| 4,4'-Methylene bis(phenylisocyanate) | CEILING | 0.01 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 0.005 ppm | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 4,4'-Methylene bis(phenylisocyanate) | TWAEV | 0.005 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | CEV | 0.02 ppm | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |



Revision Date: 10/07/2015

| 4,4'-Methylene bis(phenylisocyanate) | TWA | 0.005 ppm | 0.051 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
|---|---------|-----------|----------------|---|
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 1,2,4-Trimethylbenzene | TWAEV | 25 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| 1,2,4-Trimethylbenzene | TWA | 25 ppm | 123 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
| Polymethylene polyphenyl isocyanate | TWA | 0.005 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | CEILING | 0.01 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | TWA | 0.005 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| | CEILING | 0.01 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Polymethylene polyphenyl isocyanate | TWAEV | 0.005 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| | CEV | 0.02 ppm | ita . | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |



Revision Date: 10/07/2015

| Polymethylene polyphenyl isocyanate | TWA | 0.005 ppm | 0.051 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |
|---|-------|-----------|----------------|---|
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| 1,3,5-Trimethylbenzene | TWAEV | 25 ppm | | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| 1,3,5-Trimethylbenzene | TWA | 25 ppm | 123 mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12, 2008) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction. | TWA | | 0.025 mg/m3 | Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable. | TWAEV | | 0.10 mg/m3 | Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010) |
| Crystalline Silica (Quartz)/ Silica Sand - Respirable dust. | TWA | 0.1 | mg/m3 | Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (12 2008) |

Appropriate Engineering Controls

Mechanical ventilation or local exhaust ventilation may be required.

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of dust.

Individual protection measures, such as personal protective equipment

General information:

Use personal protective equipment as required.

Eye/face protection:

Wear goggles/face shield.

Skin Protection

Hand Protection:

Use suitable protective gloves if risk of skin contact.

Other:

Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge or canister. Contact health and safety professional or

manufacturer for specific information.

Hygiene measures:

Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with skin.

8/17



Revision Date: 10/07/2015

9. Physical and chemical properties

Appearance

Physical state:

solid

Form:

Paste

Color:

Grav

Odor: Odor threshold: Mild No data available.

No data available.

pH:

No data available.

Melting point/freezing point: Initial boiling point and boiling range:

No data available.

Flash Point:

No data available.

Evaporation rate:

Slower than n-Butyl Acetate

Flammability (solid, gas):

No

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

No data available.

Flammability limit - lower (%):

No data available.

Explosive limit - upper (%):

No data available.

Explosive limit - lower (%): Vapor pressure:

No data available. No data available.

Vapor density:

Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density:

1.1344

Solubility(ies)

Solubility in water:

Insoluble in water

Solubility (other):

No data available.

Partition coefficient (n-octanol/water):

No data available.

Auto-ignition temperature:

No data available.

Decomposition temperature:

No data available.

Viscosity:

No data available.

10. Stability and reactivity

Reactivity:

No data available.

Chemical Stability:

Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid:

Avoid heat or contamination.

Incompatible Materials:

Hazardous Decomposition

Alcohols. Amines. Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases. Water, moisture.

Thermal decomposition or combustion may liberate carbon oxides and

Products:

other toxic gases or vapors.



Revision Date: 10/07/2015

11. Toxicological information

Information on likely routes of exposure

Ingestion:

May be ingested by accident. Ingestion may cause irritation and malaise.

Inhalation:

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact:

Causes mild skin irritation. May cause an allergic skin reaction.

Eye contact:

Eye contact is possible and should be avoided.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:

ATEmix: 40,237.64 mg/kg

Dermal

Product:

ATEmix: 8,270.65 mg/kg

Inhalation

Product:

No data available.

Repeated dose toxicity

Product:

No data available.

Skin Corrosion/Irritation

Product:

No data available.

Serious Eye Damage/Eye Irritation

Product:

No data available.

Specified substance(s):

Heavy aromatic naphtha

in vivo (Rabbit, 24 - 72 hrs): Not irritating

Titanium dioxide

in vivo (Rabbit, 24 - 72 hrs): Not irritating

Aromatic petroleum

distillates

in vivo (Rabbit, 24 - 72 hrs): Not irritating

4,4'-Methylene

bis(phenylisocyanate)

in vivo (Rabbit, 24 - 72 hrs): Not irritating

1,2,4-Trimethylbenzene

in vivo (Rabbit, 30 min): Not irritating

Aluminum oxide

in vivo (Rabbit, 24 hrs): Not irritating

1,3,5-Trimethylbenzene

in vivo (Rabbit, 30 min): Not irritating



Revision Date: 10/07/2015

Respiratory or Skin Sensitization

Product:

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause sensitization by inhalation.

Carcinogenicity

Product:

No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Titanium dioxide

Overall evaluation: Possibly carcinogenic to humans.

Crystalline Silica

(Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans,

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline

Silica Known To Be Human Carcinogen.

(Quartz)/

Sand

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Silica

Germ Cell Mutagenicity

In vitro

Product:

No data available.

In vivo

Product:

No data available.

Reproductive toxicity

Product:

No data available.

Specific Target Organ Toxicity - Single Exposure

Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product:

No data available.

Aspiration Hazard

Product:

No data available.

Other effects:

No data available.



Revision Date: 10/07/2015

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:

No data available.

Specified substance(s):

Titanium dioxide

LC 50 (Mummichog (Fundulus heteroclitus), 96 h): > 1,000 mg/l Mortality

1,2,4-Trimethylbenzene

LC 50 (Fathead minnow (Pimephales promelas), 96 h): 7.19 - 8.28 mg/l

Mortality

1,3,5-Trimethylbenzene

LC 50 (Goldfish (Carassius auratus), 96 h): 9.89 - 15.05 mg/l Mortality

Aquatic Invertebrates

Product:

No data available.

Specified substance(s):

Titanium dioxide

EC 50 (Water flea (Daphnia magna), 48 h): > 1,000 mg/l Intoxication

1,2,4-Trimethylbenzene

LC 50 (Scud (Elasmopus pectinicrus), 24 h): 4.89 - 5.62 mg/l Mortality

1,3,5-Trimethylbenzene

EC 50 (Water flea (Daphnia magna), 24 h): 50 mg/l Intoxication

Chronic hazards to the aquatic environment:

Flsh

Product:

No data available.

Specified substance(s):

Heavy aromatic naphtha

NOAEL (Oncorhynchus mykiss, 28 d): 0.098 mg/l QSAR

Titanium dioxide

LC 0 (Coregonus autumnalis migratorius G., 30 d): 3 mg/l experimental

result

Aromatic petroleum

distillates

NOAEL (Daphnia magna, 21 d): 2.6 mg/l read across

Aluminum oxide

NOAEL (Pimephales promelas, 28 d): 4.7 mg/l experimental result

Aquatic Invertebrates

Product:

No data available.

Toxicity to Aquatic Plants

Product:

No data available.

Persistence and Degradability

Biodegradation

Product:

No data available.



Revision Date: 10/07/2015

BOD/COD Ratio

Product:

No data available.

Bioaccumulative Potential

Bioconcentration Factor (BCF)

Product:

No data available.

Partition Coefficient n-octanol / water (log Kow)

Product:

No data available.

Mobility in Soil:

No data available.

Other Adverse Effects: Very toxic to aquatic organisms.

13. Disposal considerations

Disposal instructions:

Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging:

No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.



Revision Date: 10/07/2015

CERCLA Hazardous Substance List (40 CFR 302.4):

| Chemical Identity | Reportable quantity |
|--------------------------|---------------------|
| 4,4'-Methylene | 5000 lbs. |
| bis(phenylisocyanate) | |
| Polymethylene | 5000 lbs. |
| polyphenyl isocyanate | |
| 2,4-Toluene diisocyanate | 100 lbs. |
| Cumene | 5000 lbs. |
| Naphthalene | 100 lbs. |
| Xylene | 100 lbs. |
| Toluene-2,6-Diisocyanate | 100 lbs. |
| Ethylbenzene | 1000 lbs. |

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard Immediate (Acute) Health Hazards

SARA 302 Extremely Hazardous Substance

| | Reportable | |
|--------------------------|------------|-----------------------------|
| Chemical Identity | quantity | Threshold Planning Quantity |
| 2,4-Toluene diisocyanate | 100 lbs. | 500 lbs. |
| Toluene-2,6-Diisocyanate | 100 lbs. | 100 lbs. |

SARA 304 Emergency Release Notification

| Chemical Identity | Reportable quantity |
|--------------------------|---------------------|
| Diisodecyl phthalate | |
| 4,4'-Methylene | 5000 lbs. |
| bis(phenylisocyanate) | |
| Polymethylene | 5000 lbs. |
| polyphenyl isocyanate | |
| 2,4-Toluene diisocyanate | 100 lbs. |
| Cumene | 5000 lbs. |
| Naphthalene | 100 lbs. |
| Xylene | 100 lbs. |
| Toluene-2,6-Diisocyanate | 100 lbs. |
| Ethylbenzene | 1000 lbs. |



Revision Date: 10/07/2015

SARA 311/312 Hazardous Chemical

| Chemical Identity | Threshold Planning Quantity |
|------------------------------|--|
| 2,4-Toluene diisocyanate | 500lbs |
| Toluene-2,6-Diisocyanate | 100lbs |
| Calcium Carbonate | 500 lbs |
| (Limestone) | |
| Heavy aromatic naphtha | 500 lbs |
| Titanium dioxide | 500 lbs |
| Aromatic petroleum | 500 lbs |
| distillates | |
| 4,4'-Methylene | 500 lbs |
| bis(phenylisocyanate) | |
| 1,2,4-Trimethylbenzene | 500 lbs |
| Polymethylene polyphenyl | 500 lbs |
| isocyanate | partition in the contract of t |
| Aluminum oxide | 500 lbs |
| 1,3,5-Trimethylbenzene | 500 lbs |
| Crystalline Silica (Quartz)/ | 500 lbs |
| Silica Sand | |

SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

| Chemical Identity | Reportable quantity |
|--------------------------|---------------------|
| 2,4-Toluene diisocyanate | 10000 lbs |
| Toluene-2,6-Diisocyanate | 10000 lbs |

US State Regulations

US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Calcium Carbonate (Limestone)
Heavy aromatic naphtha
Titanium dioxide

US. Massachusetts RTK - Substance List

Chemical Identity

Calcium Carbonate (Limestone)
Heavy aromatic naphtha
Titanium dioxide
Crystalline Silica (Quartz)/ Silica Sand
2,4-Toluene diisocyanate
Toluene-2,6-Diisocyanate



Revision Date: 10/07/2015

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Diisodecyl phthalate Calcium Carbonate (Limestone) Heavy aromatic naphtha Titanium dioxide

US. Rhode Island RTK

Chemical Identity Diisodecyl phthalate

Other Regulations:

Regulatory VOC (less water 70 g/l and exempt solvent):

VOC Method 310:

1.78 %

Inventory Status:

Australia AICS:

One or more components in this product are not listed on or exempt from the Inventory.

Canada DSL Inventory List:

All components in this product are listed on or

exempt from the Inventory.

EINECS, ELINCS or NLP:

One or more components in this product are

not listed on or exempt from the Inventory.

Japan (ENCS) List:

One or more components in this product are not listed on or exempt from the Inventory.

China Inv. Existing Chemical Substances:

One or more components in this product are not listed on or exempt from the Inventory.

Korea Existing Chemicals Inv. (KECI):

One or more components in this product are not listed on or exempt from the Inventory.

Canada NDSL Inventory:

One or more components in this product are not listed on or exempt from the Inventory.

Philippines PICCS:

One or more components in this product are not listed on or exempt from the Inventory.

US TSCA Inventory:

All components in this product are listed on or exempt from the Inventory.

New Zealand Inventory of Chemicals:

One or more components in this product are not listed on or exempt from the Inventory.

Japan ISHL Listing:

One or more components in this product are not listed on or exempt from the Inventory.



Revision Date: 10/07/2015

Japan Pharmacopoeia Listing:

One or more components in this product are not listed on or exempt from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date:

10/07/2015

Version #:

1.0

Further Information:

No data available.

Disclaimer:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject

to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.