



**DEV TREMLASTIC SP 5 GAL DEV TREMLASTIC SP 5 GAL**

Version 2

Print Date 07/20/2010

REVISION DATE: 03/26/2010

**SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : DEV TREMLASTIC SP 5 GAL DEV TREMLASTIC SP 5 GAL  
 Product code : DEVT962BK 805  
  
 COMPANY : Tremco Incorporated  
 3735 Green Road  
 Cleveland, OH 44122  
  
 Telephone : (216) 292-5000 8:30 - 5:00 EST  
 Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST  
 After Hours: Chemtrec 1-800-424-9300

RECEIVED KCD 10 JUL 27 PM 3:30

**SECTION 2 - HAZARDS IDENTIFICATION**

**Emergency Overview**

Brown to Black. Liquid. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.  
 Eyes : Direct contact may cause mild irritation.  
 Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.  
 Skin : May cause mild irritation. May cause sensitization resulting in irritation, itching and redness. May cause a rash.

**Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Prolonged or repeated skin contact with asphalt may result in skin sensitivity, such as irritation, rashes, and dermatitis. Prolonged or repeated exposure to polycyclic aromatic hydrocarbons and other volatiles which are contained in trace amounts in asphalt have been shown to cause cancer or respiratory damage in animals. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung

**SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	40.0 - 70.0
Asphalt	8052-42-4	40.0 - 70.0
Poly (2-Chloro-1,3-Butadiene) and Copolymers	NJ TSRN# 51721300-6306P	3.0 - 7.0
Hectorite Clay	12173-47-6	1.0 - 5.0
Wood rosin	8050-09-7	0.1 - 1.0

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.



**DEV TREMLASTIC SP 5 GAL DEV TREMLASTIC SP 5 GAL**

Version 2.

Print Date 07/20/2010

REVISION DATE: 03/26/2010

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5 - FIRE FIGHTING MEASURES**

- Flash point : Not available.
- Method : Not applicable.
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide and carbon dioxide can form. Oxides of sulfur can form.
- Protective equipment for firefighters : Not applicable. Product is not expected to burn.
- Fire and explosion conditions : Not applicable, not expected to burn.

**SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

**SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to reduce exposure.
- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Other equipment not normally required.

**DEV TREMLASTIC SP 5 GAL DEV TREMLASTIC SP 5 GAL**

Version 2.

Print Date 07/20/2010

REVISION DATE: 03/26/2010

Engineering measures : General ventilation is sufficient. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

Chemical Name	CAS Number	Regulation	Limit	Form
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form : Liquid  
 Color : Brown to Black  
 Odor : Asphalt  
 pH : 9 - 10  
 Vapour pressure : Not available.  
 Vapor density : Heavier than air  
 Melting point/range : Not available.  
 Freezing point : 32 °F, 0 °C  
 Boiling point/range : Not available.  
 Water solubility : Dispersible  
 Specific Gravity : 1.03  
 % Volatile Weight : 48 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Oxidizing agents.  
 Stability : Material is stable under normal storage, handling, and use.  
 Hazardous polymerization : Will not occur under normal conditions.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of waste in compliance with state and local regulations.



**DEV TREMLASTIC SP 5 GAL DEV TREMLASTIC SP 5 GAL**

Version 2.

Print Date 07/20/2010

REVISION DATE: 03/26/2010

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**

NOT REGULATED

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.  
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:**

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

**OSHA Hazardous Components :**

Asphalt	8052-42-4
Wood rosin	8050-09-7

OSHA Status: Considered : Irritant  
hazardous based on the  
following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and  
exempt solvent) : 5 g/l

VOC Method 310 : 0 %

**U.S. State Regulations:**

MASS RTK Components	: Asphalt	8052-42-4
Penn RTK Components	: Water	7732-18-5
	Asphalt	8052-42-4
	Poly (2-Chloro-1,3-Butadiene) and Copolymers	NJ TSRN# 51721300-6306P
NJ RTK Components	: Water	7732-18-5
	Asphalt	8052-42-4
	Poly (2-Chloro-1,3-Butadiene) and Copolymers	NJ TSRN# 51721300-6306P
	Hectorite Clay	12173-47-6

Components under California Proposition 65:

**WARNING!** Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm



**DEV TREMLASTIC SP 5 GAL DEV TREMLASTIC SP 5 GAL**

Version 2

Print Date 07/20/2010

REVISION DATE: 03/26/2010

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	1
Flammability	1
Reactivity	0
PPE	

- 0 = Minimum
- 1 = Slight
- 2 = Moderate
- 3 = Serious
- 4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Rich Mikol**

**Legend**

- ACGIH - American Conference of Governmental Hygienists
- CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
- DOT - Department of Transportation
- DSL - Domestic Substance List
- EPA - Environmental Protection Agency
- HMIS - Hazardous Materials Information System
- IARC - International Agency for Research on Cancer
- MSHA - Mine Safety Health Administration
- NDSL - Non-Domestic Substance List
- NIOSH - National Institute for Occupational Safety and Health
- NTP - National Toxicology Program
- OSHA - Occupational Safety and Health Administration

- PEL - Permissible Exposure Limit
- RCRA - Resource Conservation and Recovery Act
- RTK - Right To Know
- SARA - Superfund Amendments and Reauthorization Act
- STEL - Short Term Exposure Limit
- TLV - Threshold Limit Value
- TSCA - Toxic Substances Control Act
- TWA - Time Weighted Average
- V - Volume
- VOC - Volatile Organic Compound
- WHMIS - Workplace Hazardous Materials Information System